

Technical Data Sheet

Page 1 of 1

Properties:	AKEMI® Primer AP 20 is a 1-component primer for AKEMI® silicones to improve adhesion.
Application Area:	AKEMI® Primer AP 20 is used to prime joint flanks before application of AKEMI® silicones on metallic surfaces such as zinc, eloxal and stainless steel. Used in areas indoors and outdoors for wall-, floor- and ceiling joints to improve adhesion of silicone sealants.
Instructions for Use:	1. Contact areas must be dry, clean and free of dust and grease. 2. Apply with a brush on clean and dry surface. 3. Protect treated surfaces against humidity and dust 4. After open time of 30 – 60 minutes the silicone sealant can be applied.
Special Notes:	- In order to prevent stains do not apply primer on visible areas. - Tools can be cleaned with AKEMI® Universal Diluent. - For adequate waste disposal container must be completely emptied.
Storage:	6 months in a cool place.
Health & Safety:	Read Material Safety Data Sheet before handling or using this product.
Important Notice:	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 11.15