

### Specification sheet

page 1 of 1

- Properties:** AKEMI® Exhaust Mounting Paste is a sealing paste on the basis of water glass and is free of asbestos. The product is characterized by the following properties:
- easy application
  - is hardened by the heat of the exhaust
  - high gas tightness
  - high heat resistance (approx. 700°C)
  - prevents parts rusting together, therefore easy to separate later
  - free of solvents and asbestos
- Application areas:** AKEMI® Exhaust Mounting Paste is used to seal connections in the car exhaust or flues in domestic heating systems. In addition, it prevents parts from rusting together. This enables you to separate them again later without any difficulty.
- Instructions for use:**
1. The parts to be joined must be free of rust, grease, oil and dust.
  2. Apply AKEMI® Exhaust Mounting Paste liberally and then push the parts together.
  3. AKEMI® Exhaust Mounting Paste can be made more pliant with a little water.
- Special notices:**
- Wear protective gloves when working with the product.
  - Objects which have been soiled with AKEMI® Exhaust Mounting Paste can be cleaned with water.
- Safety notices** Please refer to the EC safety data sheet
- Technical specifications:**
- |                         |   |
|-------------------------|---|
| colour:                 | beige   |
| density:                | approx. 1.63 g/cm <sup>3</sup>  |
| temperature resistance: | approx. 700°C   |
| shelf life:             | can be stored for approx. 1 year in the closed original container under cool and frost-free conditions. |
- Notice:** The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TIS 08.02