

Technical Instruction Sheet

Page 1 of 1

- Characteristics:** AKEMI® Radiator Leak Sealant is a watery dispersion of special organic binding agents. This product is characterized by the following properties:
- suitable for all types of radiators
 - compatible with all kinds of antifreeze
 - does not clog up any pipes
 - is not aggressive towards the water hoses or metals in the cooling system
- Application areas:** AKEMI® Radiator Leak Sealant is used to seal hair cracks in the car cooling system fast and for a long time.
- Instructions for use:**
1. Shake the container well before use.
 2. Add the Radiator Leak Sealant to the warm cooling water and then top up the radiator with water.
 3. Let the motor run at low revolutions for approx. 10 minutes.
 4. If necessary, top up the radiator again.
 5. The Radiator Leak Sealant remains in the cooling circuit.
- Special remarks:**
- Be careful! Danger of scalding if the cooling system has been in recent operation
 - Keep out of the reach of children.
 - Dispose of the container correctly by emptying it completely first.
 - If you change the cooling water add Radiator Leak Sealant again.
- Technical specifications:**
- | | |
|-------------------|---|
| colour | : brown |
| consistency | : liquid |
| density | : approx. 1 g/cm ³ |
| quantity required | : 125 ml for 5 to 8 l cooling water |
| shelf life | : can be stored for approx. 1 year in the closed original container if kept cool and dry. |
- Safety notices:** Please refer to the EC safety data sheet.
- Notice:** The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TIS 11.07