

Telescopic - horizontal outlet

Product information for the product group





- Hygienic design following EN 1672, EN ISO 14159 and EHEDG document 8, 13 and 44
- Certified according to EN 1253-1

- ACO Product benefits
- Fully inspectable and cleanable
- Fully removable and easily cleanable stainless steel foul air trap (FAT)
- Full drainability
- Internal radii equal or larger than 3 mm
- Fully welded hygienic joints
- Steel thickness min. 1,5 mm
- Fully pickled and passivated

- Available in 1.4301 (304) or 1.4404 (316L) grades of stainless steel
- Outlet diameter 75 or 110 mm
- Suitable for all floor types including vinyl flooring
- Location flange or integrated membrane flange for either adhesive bonding or mechanical clamp
- Telescopic friction ring included
- Adjustable EasyFix levelling feet

Item Technical Data 408075

Flange design	Outlet diameter □ [mm]	Odour trap	Material
Adhesive bonding flange	75	With	1.4301

Accessories

	Description	Used with	Description	Item number
8	Silt basket	■ ACO gully 157 - vertical □ Fixed height or elescopic ■ ACO hygenic box channel □ Channel dimension □ Width Wo [mm]: 300, 400, 500, 600, 800 □ Outlet ØD [mm]: 142 or welded with ACO hygienic gully 157 □ Direction of gully outlet: vertical	Stainless steel0,6 litre capacity	
			Material grade 1.4301 (304)	416904
			Material grade 1.4404 (316L)	416905

Item number: 408075 Version: 19.10.2018 Page 1 of 2

	Description	Used with	Description	Item number
		 ACO hygienic gully 157 Fixed height, vertica Telescopic, vertical 	 Fixed height, vertical Telescopic, vertical Made from 1.4404 (316) grade of stainless steel NBR 	
	ACO fire resistant kit for gully 157/DN 75			416932
	ACO fire resistant kit for gully 157/DN 110			416933
		ACO hygienic gully 157Gully top 250x250	Stainless steelMaterial grade 1.4301 (304)	413546

You can find further accessories under → /408075

Item number: 408075 Version: 19.10.2018 Page 2 of 2