

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Akepox 1016 Micro Filler Comp. B**

Article number: 11790, 11793, 11796, 11787

UFI: JFG2-Q0C4-K00Q-GK3A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Hardening agent/ Curing agent
Epoxy resin adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960

Fax. +49(0)911-644456

e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05

Signal word

Danger

Hazard-determining components of labelling:

reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia

Hazard statements

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

P260

Do not breathe vapours.

P273

Avoid release to the environment.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Chemical characterisation: Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Reg.nr.: 01-2119557899-12	reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Chronic 3, H412	50-100%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	12.5-25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Take affected persons out into the fresh air. Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty
Dizziness
Headache
Dizziness
Gastric or intestinal disorders
Allergic reactions
Asthma attacks
Nausea
Danger of impaired breathing.

· Hazards

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 2)

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures· **5.1 Extinguishing media**

· Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

SECTION 6: Accidental release measures· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**· Storage:· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 3)

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Protect from frost.
Store receptacle in a well ventilated area.
Keep container tightly sealed.
- Storage class: 8 A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs****reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia**

Oral	DNEL (Langzeit-wiederholt)	0.04 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	0.623-2.5 mg/kg bw/day (ARB) 0.311-1.25 mg/kg bw/day (BEV)

100-51-6 Benzyl alcohol

Oral	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	40 mg/kg bw/day (ARB) 20 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	8 mg/kg bw/day (ARB) 4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	110 mg/m³ Air (ARB) 27 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	22 mg/m³ Air (ARB) 5.4 mg/m³ Air (BEV)

· **PNECs****reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia**

PNEC (wässrig)	7.5 mg/l (KA) 0.0143 mg/l (MW) 0.015 mg/l (SW)
PNEC (fest)	0.0176 mg/kg Trockengew (BO) 0.125 mg/kg Trockengew (MWS) 0.132 mg/kg Trockengew (SWS)

100-51-6 Benzyl alcohol

PNEC (wässrig)	39 mg/l (KA) 0.1 mg/l (MW) 1 mg/l (SW) 2.3 mg/l (WAS)
PNEC (fest)	0.456 mg/kg Trockengew (BO) 0.527 mg/kg Trockengew (MWS) 5.27 mg/kg Trockengew (SWS)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 4)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

ARRETIL (<http://www.stoko.com>)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (<http://debstoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 5)

- Penetration time of glove material Value for the permeation: Level $\leq$ 6; 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Camatril (KCL, Art_No. 730, 731, 732, 733)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)
- As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye protection:  Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

<u>Form:</u>	Fluid
<u>Colour:</u>	Colourless
<u>Odour:</u>	Ammonia-like

· Change in condition

<u>Melting point/freezing point:</u>	Undetermined.
<u>Initial boiling point and boiling range:</u>	205 °C

<u>Flash point:</u>	101 °C
---------------------	--------

<u>Ignition temperature:</u>	435 °C
------------------------------	--------

<u>Auto-ignition temperature:</u>	Product is not selfigniting.
-----------------------------------	------------------------------

<u>Explosive properties:</u>	Product does not present an explosion hazard.
------------------------------	---

· Explosion limits:

<u>Lower:</u>	1.3 Vol %
<u>Upper:</u>	13 Vol %

<u>Vapour pressure at 20 °C:</u>	0.1 hPa
----------------------------------	---------

<u>Density at 20 °C:</u>	1 g/cm ³
--------------------------	---------------------

<u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
--	-----------------------------------

<u>Viscosity:</u>	
<u>Dynamic:</u>	Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	24.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Strong exothermic reaction with acids.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Nitrogen oxides
Nitrogen oxides (NOx)
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	4,333 mg/kg
Dermal	LD50	8,333 mg/kg (rabbit)
Inhalative	LC50/4 h	45.8 mg/l (rat)

reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia

Oral	LD50	2,885.3 mg/kg (rat)
	NOAEL-Werte	30 mg/kg (rat)
Dermal	LD50	2,979.7 mg/kg (rabbit)
Inhalative	LC50/8h	>0.74 mg/l (rat)

100-51-6 Benzyl alcohol

Oral	LD50	1,040 mg/kg (mouse) 1,040 mg/kg (rabbit) 1,620 mg/kg (rat)
	NOEL	400 mg/kg (rat)
	NOAEL	200 mg/kg (mouse)
Dermal	LD50	400 mg/kg (rat) 2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	11 mg/l (rat)
	LC50/48h	360 mg/l (daphnia magna) 645 mg/l (goo)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 7)

- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia

EC50/96h	>15 mg/l (piscis)
EC50/48h	80-418.34 mg/l (daphnia magna)
ErC50/72h	15 mg/l (green alge)
NOEC	0.32 mg/kg (green alge)
	310 mg/kg (bacteria)
EC50/72h	141.72 mg/l (green alge)
LC50/96h	772.14 mg/l (piscis)

100-51-6 Benzyl alcohol

EC50/24h	55-400 mg/l (daphnia magna)
EC50/96h	640 mg/l (Scenedesmus pluvialis)
EC50	2,100 mg/l (BES) (OECD 209)
	79 mg/l (Scenedesmus quadricauda)
EC10/16h	658 mg/l (pseudomonas putida)
EC50/48h	230 mg/l (daphnia magna) (OECD 202)
EC0	640 mg/l (Scenedesmus quadricauda)
EC50/16h	658 mg/l (pseudomonas putida)
EC50/30min	71.4 mg/l (Photobac. phosphoreum)
	400 mg/l (pseudomonas putida)
IC5/96h	640 mg/l (Scenedesmus quadricauda)
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)
NOEC/21d	51 mg/l (daphnia magna) (OECD211)
EC50/72h	770 mg/l (green alge) (OECD 201)
	770 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	645 mg/l (goo)
	10 mg/l (Iepomis macrochirus)
	460 mg/l (Pimephales promelas)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· PBT:

Not applicable.

· vPvB:

Not applicable.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 8)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations· **13.1 Waste treatment methods**· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents:

Diluted caustic solution.

SECTION 14: Transport information· **14.1 UN-Number**· ADR, IMDG, IATA

UN2735

· **14.2 UN proper shipping name**· ADR2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(polyoxyalkylendiamine)· IMDG, IATAPOLYAMINES, LIQUID, CORROSIVE, N.O.S.
(polyoxyalkylendiamine)· **14.3 Transport hazard class(es)**· ADR· Class

8 (C7) Corrosive substances.

· Label

8

· IMDG, IATA· Class

8 Corrosive substances.

· Label

8

· **14.4 Packing group**· ADR, IMDG, IATA

III

· **14.5 Environmental hazards:**· Marine pollutant:

No

· **14.6 Special precautions for user**· Hazard identification number (Kemler code):

Warning: Corrosive substances.

80

· EMS Number:

F-A,S-B

· Stowage Category

A

· Segregation Code

SG35 Stow "separated from" SGG1-acids

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B

(Contd. of page 9)

· Transport/Additional information:

· ADR

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

3

· Tunnel restriction code

E

· IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYALKYLENDIAMINE), 8, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I

None of the ingredients is listed.

· REGULATION (EC) No 1907/2006

ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· VOC EU

240.0 g/l

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for alterations

· Relevant phrases

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H412 Harmful to aquatic life with long lasting effects.
refer to Technical Data Sheet (TDS)

· Recommended restriction of use

· Department issuing SDS:

Laboratory

· Contact:

Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2020

Version number 2

Revision: 14.12.2020

Trade name: Akepox 1016 Micro Filler Comp. B· Abbreviations and acronyms:

(Contd. of page 10)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity - oral – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC