Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **Akepox 3000 Component A** · Article number: 10638, 10561, 10562, 10575

 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the

mixture

Epoxy resin adhesive

· 1.3 Details of the supplier of the safety data sheet

AKEMI chemisch technische Spezialfabrik GmbH Manufacturer/Supplier:

> Lechstrasse 28 D 90451 Nürnberg

Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de

· Further information obtainable

from:

Laboratory

· 1.4 Emergency telephone

number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

+44 (171) 635 91 91

National Poison Inform. Centre Medical Toxicology Unit

Avalonley Road London SE14 5ER

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 · Hazard pictograms

The product is classified and labelled according to the CLP regulation.





GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzy]]phenoxy}methyl)oxirane and [2,2'-

[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

· ·			
rade name: Akepox 3000 Com	ponent A		
			(Contd. of page 1
· Hazard statements	H315 Causes s	kin irritation.	, , , ,
	H319 Causes s	erious eye irritation.	
		e an allergic skin reaction.	
		quatic life with long lasting effects.	
· Precautionary statements	P101	If medical advice is needed, have p at hand.	roduct container or labe
	P102	Keep out of reach of children.	
	P103	Read label before use.	
	P261	Avoid breathing vapours.	
	P273	Avoid release to the environment.	
	P280	Wear protective gloves/protective clc protection.	othing/eye protection/face
	P302+P352	IF ON SKIN: Wash with plenty of wat	er.
		38 IF IN EYES: Rinse cautiously with w	
	. 00011 00111	Remove contact lenses, if present a rinsing.	
	P333+P313	If skin irritation or rash occurs: Get m	edical advice/attention
	P337+P313	If eye irritation persists: Get medical	
	P501	Dispose of contents/container in	
		regional/national/international regular	
· 2.3 Other hazards		rogrammanoma, material rogana	
Results of PBT and vPvB asse	essment		
· PBT:	Not applicable.		
· vPvB:	Not applicable.		

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	50-100%
EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg.nr.: 01-2119454392-40-0003	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)] dioxirane	
	Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	
. Additional information:	For the wording of the listed hazard phrases refer to section 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

• After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

(Contd. on page 3)



(Contd. of page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

Rinse out mouth and then drink plenty of water.

 After swallowing: · 4.2 Most important symptoms and effects, both acute and

delayed

Breathing difficulty

Coughing Allergic reactions

Bisphenol-A based resins: Inhalation, swallowing or dermal incorporation may Information for doctor:

cause health damage. Irritates respiratory tract, digestion system, eyes and skin: e.g., cough, dyspnea, lacrimation, burning. May cause health interferences such as dermal changes, renal, hepatic damage, and blood count changes. May provoke skin allergies. Sensitized users can react towards very low concentrations of Bisphenol-A-Epichlorhydrine and should avoid any further

contact with this chemical.

The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight \leq 300. The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.

Danger of impaired breathing.

Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer

on the skin were applied.

· 4.3 Indication of any immediate medical attention and special

treatment needed

· Hazards

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

 Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· 5.3 Advice for firefighters

Wear fully protective suit. · Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

· 6.2 Environmental precautions: Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

(Contd. of page 3)

· 6.3 Methods and material for

containment and cleaning up:

Do not allow to enter sewers/ surface or ground water.

Dispose of the material collected according to regulations. Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection:

No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from reducing agents. Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that

require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

· DNELs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane DNEL (Kurzzeit-akut)

Orai	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB)
		0.0893 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m³ Air (ARB)

DNEL (Langzeit-wiederholt) 4.93 mg/m³ Air (ARB) 0.87 mg/m³ Air (BEV)

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

(Contd. of page 4)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-
ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	DNEL (Langzeit-wiederholt)	6.25 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	mg/kg bw/day (ARB)
		62.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	29.39 mg/m³ Air (ARB)
		8.7 mg/m³ Air (BEV)

· PNECs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

PNEC (wässrig) 10 mg/l (KA)
0.0006 mg/l (MW)
0.006 mg/l (SW)
0.018 mg/l (WAS)
PNEC (fest) 0.065 mg/kg Trockengew (BO)
0.034 mg/kg Trockengew (MWS)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

PNEC (wässrig) 10 mg/l (KA)

0 mg/l (MW) 0.003 mg/l (SW) 0.025 mg/l (WAS)

PNEC (fest) 0.237 mg/kg Trockengew (BO)

0.029 mg/kg Trockengew (MWS) 0.294 mg/kg Trockengew (SWS)

0.341 mg/kg Trockengew (SWS)

· Additional information:

· Protection of hands:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

- General protective and hygienic

measures: Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

• Respiratory protection: Not necessary if room is well-ventilated.

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves: STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

(Contd. of page 5)

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

<u>Material of gloves</u>
 Butyl rubber, BR

Chloroprene rubber, CR Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Nitrile rubber, NBR

Camatril (KCL, Art_No. 730, 731, 732, 733)

Dermatril (Art_No. 740, 741, 742)

Chloroprene rubber, CR

Camapren (KCL, Art_No. 720, 722, 726)

 As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Dermatril (KCL, Art_No. 740, 741, 742) Camatril (KCL, 730, 731, 732, 733)

 Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty

Colour: Different according to colouring

- Odour: Characteristic

· pH-value: Not applicable

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: > 200 °C

· Flash point: Not applicable.

· Ignition temperature: 370 °C

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Vapour pressure at 20 °C: 2 hPa

- Density at 20 °C: 1.18 g/cm³

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.0 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition /

<u>conditions to be avoided:</u> No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous

reactions May produce violent reactions with bases and numerous organic substances

including alcohols and amines. Reacts with reducing agents.

Reacts with strong acids.

• 10.4 Conditions to avoid No further relevant information available. No further relevant information available.

· 10.6 Hazardous decomposition

products: Irritant gases/vapours

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral LD50 15,000 mg/kg (rat)

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

Dermal LD50 23,000 mg/kg (rabbit)

(Contd. of page 7)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral LD50 >5,000 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rat)

· Primary irritant effect:

Skin corrosion/irritation
 Serious eye damage/irritation
 Respiratory or skin sensitisation
 CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

IC50 >100 mg/l (BES)

EC10/16h 100 mg/l (pseudomonas putida) EC50/48h 1.8 mg/l (daphnia magna) NOEC/21d 0.3 mg/l (daphnia magna)

EC50/72h 11 mg/l (selenastrum capricornutum) LC50/96h 2 mg/l (Oncorhynchus mykiss)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

EC50/48h | 2.55 mg/l (daphnia magna) EC50/72h | 1.8 mg/l (green alge) LC50/96h | 2.54 mg/l (piscis)

· 12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water

· 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

(Contd. of page 8)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

European waste catalogue

20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

20 01 00 separately collected fractions (except 15 01)

20 01 27* paint, inks, adhesives and resins containing hazardous substances

Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

acetone

SECTION 14: Transport information

· 14.1 UN-Number	
· <u>ADR, IMDG, IATA</u>	UN3082
· 14.2 UN proper shipping name	
· <u>ADR</u>	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane), MARINE POLLUTANT
· <u>IATA</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)
· 14.3 Transport hazard class(es)	

· ADR



Class
 Label
 9 (M6) Miscellaneous dangerous substances and articles.
 9

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

(Contd. of page 9)

· IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles.

· Label 9

· 14.4 Packing group · ADR, IMDG, IATA

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: Yes

Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles.

Hazard identification number (Kemler code):
EMS Number:
Stowage Category
90
F-A,S-F
A

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

ADR

· Limited quantities (LQ) 5L

- Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport categoryTunnel restriction code

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· <u>UN "Model Regulation":</u> UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL] PROPANE, REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE AND [2-({2-[4-(OXIRAN-2-YLMETHOXY)BENZYL]PHENOXY}METHYL) OXIRANE AND [2,2'-[METHYLENEBIS(2,1-

PHENYLENEOXYMETHYLENE)]DIOXIRANE), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation

(EC) No 1272/2008 GHS label elements

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

• Seveso category E2 Hazardous to the Aquatic Environment

(Contd. on page 11)



(Contd. of page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.05.2020 Version number 5 Revision: 27.05.2020

Trade name: Akepox 3000 Component A

Qualifying quantity (tonnes) for the

application of lower-tier

requirements 200 t

Qualifying quantity (tonnes) for the

application of upper-tier

500 t requirements

REGULATION (EC) No 1907/2006

Conditions of restriction: 3 ANNEX XVII

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

VOC EU

 $0.0 \, g/l$

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

refer to Technical Data Sheet (TDS) · Recommended restriction of use

Department issuing SDS: Laboratory

· Contact: Elke Hake

> Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de Abbreviations and acronyms:

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous

version altered. Adaptation in accordance with REACH directive 1907/2006/EC