

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **AkepoX 3015 Rapid Bond Component B**

Article number: 10798_B

UFI: RPF3-V09V-D00W-AR71

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960

Fax. +49(0)911-644456

e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

Signal word

Danger

Hazard-determining components of labelling:

Poly(oxyethyl-1, 2-ethandiyl), alpha-hydro-omega-hydroxy-, ether mit 2,2-bis(hydroxymethyl)-1,3-propandiol (4:1), 2-hydroxy-3-mercaptopropyl ether
N-(3-(trimethoxysilyl)propyl)ethylenediamine
2,4,6-tris(dimethylaminomethyl)phenol
formaldehyde polymer with 1,3-benzenedimethanamine and phenol
m-phenylenebis(methylamine)
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Hazard statements

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 1)

· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P261	Avoid breathing vapours.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P302+P352	IF ON SKIN: Wash with plenty of water.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB:

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

SECTION 3: Composition/information on ingredients· **3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 72244-98-5 EC number: 701-196-7 Reg.nr.: 01-2120118957-46-0000	Poly(oxyethyl-1, 2-ethandiol), alpha-hydro-omega-hydroxy-, ether mit 2,2-bis(hydroxymethyl)-1,3-propandiol (4:1), 2-hydroxy-3-mercaptopropyl ether Skin Sens. 1B, H317 Aquatic Chronic 3, H412	25-50%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39	N-(3-(trimethoxysilyl)propyl)ethylenediamine STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H332; Skin Sens. 1, H317 vPvB	1-5%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27-xxxx	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1B, H317 Aquatic Chronic 3, H412	1-5%
CAS: 1950616-36-0 EC number: 701-207-5 Reg.nr.: 01-2119966906-20	formaldehyde polymer with 1,3-benzenedimethanamine and phenol Skin Corr. 1B, H314; Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	1-5%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**· **4.1 Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 2)

· After inhalation:

Take affected persons out into the fresh air.

Position and transport stably in side position.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· Information for doctor:

The symptoms of phenol based poisoning appearances are white coloured mouth scabs, shock condition, insensibility, bradycardia and renal dysfunction and damage of renal tissue. Appropriate therapy measures: Administration of an adequate volume of liquid, gastrolavage in application of carbo medicinalis, sodium sulphate with plenty of water, infusion of glucose solution (5%); measures against state of shock, hemodialysis.

Amines: Inhalation, swallowing or dermal contact may cause health damages. Cause burns, harm respiratory tract, eyes, skin, and digestion system in worst case up to complete destruction. Intermediate interferences such as headache, nausea, cough, dyspnea may occur. May cause allergies. Sensitized users may react towards very low amine concentrations and should avoid any further contact with this group of chemicals.

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Headache

Coughing

Allergic reactions

Nausea

· Hazards

Danger of impaired breathing.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures· **5.1 Extinguishing media**· Suitable extinguishing agents:CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· For safety reasons unsuitable extinguishing agents:

Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

· **5.3 Advice for firefighters**· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Keep receptacles tightly sealed.
Prevent formation of aerosols.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**
Do not store together with acids.
Store away from oxidising agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
Keep container tightly sealed.
- **Storage class:**
12
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:**
No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 4)

· DNELs**1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

Oral	DNEL (Langzeit-wiederholt)	2.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	5 mg/kg bw/day (ARB)
		17 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	5 mg/kg bw/day (ARB)
Inhalative		2.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	35.3 mg/m³ Air (ARB)
		8.7 mg/m³ Air (BEV)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Inhalative	DNEL (Langzeit-wiederholt)	0.31 mg/m³ Air (ARB)
------------	----------------------------	----------------------

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

Oral	DNEL (Kurzzeit-akut)	3.33 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	3.33 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.00385-2.8 mg/kg bw/day (ARB)
		0.000167-0.008 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.000385-0.28 mg/kg bw/day (ARB)
Inhalative		0.000167-0.008 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	2-6 mg/m³ Air (ARB)
	DNEL (Langzeit-wiederholt)	0.02 mg/m³ Air (ARB)

1477-55-0 m-phenylenebis(methylamine)

Dermal	DNEL (Langzeit-wiederholt)	0.33 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	1.2 mg/m³ Air (ARB)

· PNECs**1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

PNEC (wässrig)	25 mg/l (KA)
	0.0062 mg/l (MW)
	0.062 mg/l (SW)
	0.62 mg/l (WAS)
PNEC (fest)	0.0075 mg/kg Trockengew (BO)
	0.005 mg/kg Trockengew (MWS)
	0.05 mg/kg Trockengew (SWS)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

PNEC (wässrig)	0.2 mg/l (KA)
	0.0084 mg/l (MW)
	0.084 mg/l (SW)
	0.84 mg/l (WAS)

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

PNEC (wässrig)	30 mg/l (KA)
	0.002 mg/l (MW)
	0.02 mg/l (SW)
PNEC (fest)	0.0236 mg/kg Trockengew (BO)
	0.01 mg/kg Trockengew (MWS)
	0.1001 mg/kg Trockengew (SWS)

1477-55-0 m-phenylenebis(methylamine)

PNEC (wässrig)	10 mg/l (KA)
----------------	--------------

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 5)

PNEC (fest)	0.0094 mg/l (MW)
	0.094 mg/l (SW)
	0.152 mg/l (WAS)
	0.045 mg/kg Trockengew (BO)
	0.043 mg/kg Trockengew (MWS)
	0.43 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Apply solvent resistant skin cream before starting work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A/P2

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (<http://debstoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 6)

- Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
Value for the permeation: Level ≤ 6 , 480 min
- For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
- As protection from splashes gloves made of the following materials are suitable: Natural rubber, NR
Combi-Latex (KCL, Art_No. 395)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)
Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
- Not suitable are gloves made of the following materials: Natural rubber, NR
Leather gloves
Strong material gloves
- Eye protection:  Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**General InformationAppearance:Form:

Fluid

Colour:

Green

Odour:

Like rotten eggs (mercaptans)

pH-value:

Not applicable

Change in conditionMelting point/freezing point:

Undetermined.

Initial boiling point and boiling range: Undetermined.Flash point:

Not applicable.

Auto-ignition temperature:

Product is not selfigniting.

Explosive properties:

Product does not present an explosion hazard.

Vapour pressure:

Not determined.

Density at 20 °C:1.59 g/cm³Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Viscosity:Dynamic at 20 °C:

50,000 mPas

Kinematic:

Not determined.

Solvent content:Organic solvents:

0.4 %

Solids content:

62.5 %

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 7)

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No further relevant information available.

10.2 Chemical stabilityThermal decomposition /
conditions to be avoided:

No decomposition if used according to specifications.

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with acids.

Reacts with oxidising agents.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

Nitrogen oxides

Nitrogen oxides (NO_x)

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 77,031 mg/kg (rat)

Inhalative LC50/4 h 38.6 mg/l (rat)

72244-98-5 Poly(oxyethyl-1, 2-ethandiyl), alpha-hydro-omega-hydroxy-, ether mit 2,2-bis(hydroxymethyl)-1,3-propandiol (4:1), 2-hydroxy-3-mercaptopropyl ether

Oral LD50 2,600 mg/kg (rat)

Dermal LD50 >10,200 mg/kg (rabbit)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral LD50 2,995 mg/kg (rat)

NOEL ≥500 mg/kg (rat) (OECD 422)

NOAEL ≥500 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Inhalative LC50/4 h 1.49 mg/l (rat)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Oral LD50 2,169 mg/kg (rat)

Dermal LD50 1,100 mg/kg (ATE)

LD50 >971 mg/kg (rat)

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,020 mg/kg (rat)

1477-55-0 m-phenylenebis(methylamine)

Oral LD50 <2,000 mg/kg (rat)

NOEL 150 mg/kg (rat)

Dermal LD50 3,100 mg/kg (rabbit)

Inhalative LC50/4 h 2.4 mg/l (rat)

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 8)

LC50/1h 3.89 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

· Aquatic toxicity:

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

EC50	435 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung)
IC50/72h	8.8 mg/l (green alge) (OECD 201)
EC50/48h	81 mg/l (daphnia magna)
EC50/16h	67 mg/l (pseudomonas putida)
NOEC	3.1 mg/kg (green alge) (OECD 201)
	≥1,000 mg/kg (Eisenia fetida (Regenwürmer)) (OECD 207)
NOEC/21d	>1 mg/l (daphnia magna)
EC50/48h	87.4 mg/l (daphnia magna)
EC50/72h	5 mg/l (green alge)
	126 mg/l (Scenedesmus subspicatus)
LC50/96h	344 mg/l (Brachydanio rerio)
	597 mg/l (Danio rerio.)
	168 mg/l (pimephales promelas)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

EC50/96h	718 mg/l (Palaemonetes)
LC50/24h	222 mg/l (Oncorhynchus mykiss)
ErC50/72h	84 mg/l (green alge)
NOELR/72h	6.25 mg/l (green alge)
LC50/96h	175 mg/l (Cyprinus carpio)
	718 mg/l (daphnia magna)
LC50/72h	84 mg/l (Scenedesmus subspicatus)

1950616-36-0 formaldehyde polymer with 1,3-benzenedimethanamine and phenol

EC50	491.3 mg/l (BES)
EC50/48h	29.8 mg/l (daphnia magna)
EC50/72h	20.4 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	25.9 mg/l (Oncorhynchus mykiss)

1477-55-0 m-phenylenebis(methylamine)

EC50/48h	15.2 mg/l (daphnia magna)
EC50/30min	>1,000 mg/l (BES)
NOEC/21d	4.7 mg/l (daphnia magna)

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 9)

EC50/72h	12 mg/l (Scenedesmus subspicatus)
	32.1 mg/l (selenastrum capricornutum)
LC50/96h	>100 mg/l (Oncorhynchus mykiss)
	87.6 mg/l (Oryzias latipes)
	>100 mg/l (Zebraabärbling)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:**

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· **Recommended cleansing agents:** acetone

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **UN "Model Regulation":**

Void

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

(Contd. of page 10)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -
ANNEX I

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

· VOC EU

6.9 g/l

· 15.2 Chemical safety
assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use

refer to Technical Data Sheet (TDS)

· Department issuing SDS:

Laboratory

· Contact:

Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.03.2021

Version number 8

Revision: 09.03.2021

Trade name: Akepox 3015 Rapid Bond Component B

· * Data compared to the previous
version altered.

(Contd. of page 11)

Adaptation in accordance with REACH directive 1907/2006/EC

GB