

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Akepox 5010 Component B

· Article number: 10671, 10673, 22913, 10685B, 10686B, 10684B, 10687B, 11460B, 11461B,

No further relevant information available.

11462B, 11463B, 11464B, 11465B, 11466B, 11467B, 11468B, 11469B, 11470B,

11725, 10325B

N1AA-2R3V-FY04-TGPT

· 1.2 Relevant identified uses of the substance or mixture and

uses advised against

· Application of the substance / the

mixture

Epoxy resin adhesive

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

> Lechstrasse 28 D 90451 Nürnberg

Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de

· Further information obtainable

from:

Laboratory

1.4 Emergency telephone

number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Store locked up. · Storage:

Store in a well-ventilated place. Keep container tightly closed.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 · Hazard pictograms

The product is classified and labelled according to the CLP regulation.

GHS05 GHS07

· Signal word Danger

· Hazard-determining components of

1,3-Cyclohexanedimethanamine labelling:

2,2,4-trimethylhexan-1,6-diamine

· Hazard statements H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



Page 2/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

(Contd. of page 1) If medical advice is needed, have product container or label at · Precautionary statements P101

hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsina.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. Not applicable. · vPvB:

· Determination of endocrine-

disrupting properties For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Mixture of substances listed below with nonhazardous additions. · Description:

	· Dangerous components:			
	CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	12.5-25%	
	CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-xxxx	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	<10%	
	CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-xxxx	2,2,4-trimethylhexan-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317	<10%	
· Additional information: For the wording of the listed hazard phrases refer to see				

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

(Contd. on page 3)



Page 3/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

(Contd. of page 2)

Rinse opened eye for several minutes under running water. Then consult a · After eye contact:

doctor.

 After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and

delayed

Headache Dizziness Nausea

Breathing difficulty

Coughing Danger of impaired breathing.

· Hazards · 4.3 Indication of any immediate

medical attention and special

treatment needed If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from

the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

Collect contaminated fire fighting water separately. It must not enter the sewage · Additional information

system.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class: 8

· 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that

require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

	vait	des that have to be monitored at the workplace.		
DNELs				
100-51-6 Benzyl alcohol				
Oral	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (BEV)		
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)		
Dermal	DNEL (Kurzzeit-akut)	40 mg/kg bw/day (ARB)		
		20 mg/kg bw/day (BEV)		
	DNEL (Langzeit-wiederholt)	8 mg/kg bw/day (ARB)		
		4 mg/kg bw/day (BEV)		
Inhalative	DNEL (Kurzzeit-akut)	110 mg/m³ Air (ARB)		
		27 mg/m³ Air (BEV)		
	DNEL (Langzeit-wiederholt)	22 mg/m³ Air (ARB)		
		5.4 mg/m³ Air (BEV)		
2579-20-6 1,3-Cyclohexanedimethanamine				
Inhalative	DNEL (Langzeit-wiederholt)	0.00947 mg/m³ Air (ARB)		
25513-64-	liamine			
Oral	DNEL (Langzeit-wiederholt)	0.05 mg/kg bw/day (BEV)		

(Contd. on page 5)



Page 5/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

		(Contd. of page 4)		
· PNECs	· PNECs			
100-51-6 Benzy	100-51-6 Benzyl alcohol			
PNEC (wässrig)	PNEC (wässrig) 39 mg/l (KA)			
	0.1 mg/l (MW)			
	1 mg/l (SW)			
	2.3 mg/l (WAS)			
PNEC (fest)	0.456 mg/kg Trockengew (BO)			
	0.527 mg/kg Trockengew (MWS)			
	5.27 mg/kg Trockengew (SWS)			
2579-20-6 1,3-C	2579-20-6 1,3-Cyclohexanedimethanamine			
PNEC (wässrig) 10 mg/l (KA)				
0.003 mg/l (MW)				
	0.033 mg/l (SW)			
25513-64-8 2,2,4	25513-64-8 2,2,4-trimethylhexan-1,6-diamine			
PNEC (wässrig)	0.072 mg/l (KA)			
	0.01 mg/l (MW)			
	0.102 mg/l (SW)			
	0.315 mg/l (WAS)			
PNEC (fest)	10 mg/kg Trockengew (BO)			
	0.062 mg/kg Trockengew (MWS)			
	0.662 mg/kg Trockengew (SWS)			

· Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Hand protection

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic

measures: Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection: Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation Skin protection agent recommendation for preventive skin shelter

without use of protective gloves:

(Contd. on page 6)



Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

(Contd. of page 5)

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).

Material of gloves

Butyl rubber, BR Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Nitrile rubber, NBR

Dermatril (Art No. 740, 741, 742)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Dermatril (KCL, Art_No. 740, 741, 742)

Tightly sealed goggles

· Not suitable are gloves made of the following materials:

Leather gloves

· Eye/face protection

Strong material gloves

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: Colourless Characteristic · Odour: Undetermined.

· Melting point/freezing point:

(Contd. on page 7)



Page 7/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

(Contd. of page 6)

· Boiling point or initial boiling point and boiling range	205.4 °C
Lower and upper explosion limit	
Lower:	1.3 Vol %
· Upper:	13 Vol %
· Flash point:	101 °C
A de la	405.00

435 °C · Auto-ignition temperature: Not determined. · pH Not applicable

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic at 20 °C: 8,000 mPas

· Solubility

· water: Partly soluble. · Vapour pressure at 20 °C: 0.1 hPa · Vapour pressure at 50 °C: 0.7 hPa

· Density and/or relative density

Density at 20 °C: 1.07 g/cm³

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health and environment, and on safety.

· Ignition temperature:

Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Organic solvents: 23.2 %

· Information with regard to physical hazard classes

Void · Explosives Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Void · Organic peroxides · Corrosive to metals Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

· Desensitised explosives

conditions to be avoided: No decomposition if used and stored according to specifications.

Void

· 10.3 Possibility of hazardous

reactions Strong exothermic reaction with acids. Reacts with strong oxidising agents.

(Contd. on page 8)



(Contd. of page 7)

Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

No further relevant information available.

· 10.4 Conditions to avoid · 10.5 Incompatible materials:

No further relevant information available.

· 10.6 Hazardous decomposition

products:

Corrosive gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
ATE (Acu	ATE (Acute Toxicity Estimates)		
Oral	LD50	2,437 mg/kg	
Dermal	LD50	6,268 mg/kg	
Inhalative	LC50/4 h	47.5 mg/l (rat)	

Inhalative	LC50/4 h	47.5 mg/l (rat)		
100-51-6 I	100-51-6 Benzyl alcohol			
Oral	Oral LD50 1,040 mg/kg (mouse)			
		1,040 mg/kg (rabbit)		
		1,620 mg/kg (rat)		
	NOEL	400 mg/kg (rat)		
	NOAEL	200 mg/kg (mouse)		
		400 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		
Inhalative	LC50/8h	1,000 ppm (rat)		
	LC50/4 h	>4.178 mg/l (rat) (OECD 403)		
	LC50/48h	360 mg/l (daphnia magna)		
		645 mg/l (goo)		
2579-20-6	2579-20-6 1,3-Cyclohexanedimethanamine			
Oral	LD50	>700-2,000 mg/kg (rat) (OECD 423)		
	LD0	>300 mg/kg (rat)		
	LD100	2,000 mg/kg (rat)		
Dermal	LD50	1,700 mg/kg (rabbit)		
LC50/48h 33.1 mg/l (daphnia magna)				
	25513-64-8 2,2,4-trimethylhexan-1,6-diamine			
Oral	LD50	910 mg/kg (rat)		

Oral	LD50	910 mg/kg (rat)	
	LC50/48h	174 mg/l (Leuciscus idus) (DIN 38412 Teil 15)	

· Primary irritant effect: Do not get in eyes, on skin, or on clothing.

• Skin corrosion/irritation Result of the "In vitro membrane barrier test for skin corrosion" allows

classification in subcategory 1 B (dangerous goods packaging group II).

Causes severe skin burns and eye damage.

Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)



(Contd. of page 8)

Page 9/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

12.1 Toxicity				
· Aquatic toxicity:				
100-51-6 Benzyl alcohol				
EC50/24h 55-400 mg/l (daphnia magna)				
EC50/96h	640 mg/l (Scenedesmus pluvialis)			
EC50	2,100 mg/l (BES) (OECD 209)			
	79 mg/l (Scenedesmus quadricauda)			
EC10/16h	658 mg/l (pseudomonas putida)			
EC50/48h	230 mg/l (daphnia magna) (OECD 202)			
EC0	640 mg/l (Scenedesmus quadricauda)			
EC50/16h	658 mg/l (pseudomonas putida)			
EC50/30min	71.4 mg/l (Photobac. phosphoreum)			
	400 mg/l (pseudomonas putida)			
IC5/96h	640 mg/l (Scenedesmus quadricauda)			
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)			
NOEC/21d	51 mg/l (daphnia magna) (OECD211)			
EC50/72h	770 mg/l (green alge) (OECD 201)			
	770 mg/l (Pseudokirchneriella subcapitata)			
LC50/96h	645 mg/l (goo)			
	10 mg/l (lepomis macrochirus)			
	8.9 mg/l (Oncorhynchus mykiss)			
	460 mg/l (Pimephales promelas)			
2579-20-6 1,3-Cyclohexanedimethanamine				
EC50	>1,000 mg/l (BES)			
	90 mg/l (pseudomonas putida)			
EC50/48h	65.4 mg/l (daphnia magna) (OECD 202)			
ErC50/72h	>100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)			
LC100/96h	180 mg/l (Leuciscus idus)			
NOELR/72h	14.4 mg/l (Pseudokirchneriella subcapitata) (OECD 201)			
EC50/72h	29.7 mg/l (selenastrum capricornutum)			
LC50/96h	130 mg/l (Leuciscus idus) (OECD 203)			
EBC50	58.4 mg/l (Pseudokirchneriella subcapitata)			
25513-64-8 2,2,4-trimethylhexan-1,6-diamine				
	31.5 mg/l (daphnia magna) (DIN 38412 Teil 11)			
EC50/24h	89 mg/l (pseudomonas putida)			
EC50/24h EC50				
	89 mg/l (pseudomonas putida)			
EC50				
EC50 IC50	89 mg/l (pseudomonas putida)			

on page 1



(Contd. of page 9)

Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

NOELR/21d | 1.02 mg/l (daphnia magna)

EC50/72h

43.5 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

29.5 mg/l (Scenedesmus subspicatus)

· 12.2 Persistence and

degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects · Additional ecological information:

· General notes: Do not allow undiluted product or large quantities of it to reach ground water,

water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous

for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· European waste catalogue

20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

20 01 00 separately collected fractions (except 15 01)

20 01 27* paint, inks, adhesives and resins containing hazardous substances

· Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1719

· 14.2 UN proper shipping name

· ADR 1719 CAUSTIC ALKALI LIQUID, N.O.S. (2,2,4-trimethylhexan-

1,6-diamine, 1,3-Cyclohexanedimethanamine)

· IMDG, IATA CAUSTIC ALKALI LIQUID, N.O.S. (2,2,4-trimethylhexan-1,6-

diamine, 1,3-Cyclohexanedimethanamine)

14.3 Transport hazard class(es)

· ADR



Class 8 (C5) Corrosive substances.

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B (Contd. of page 10) · Label 8 · IMDG, IATA 8 Corrosive substances. · Class · Label 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Corrosive substances. Hazard identification number (Kemler code): 80 F-A,S-B · EMS Number: · Segregation groups (SGG18) Alkalis · Stowage Category · Segregation Code SG22 Stow "away from" ammonium salts SG35 Stow "separated from" SGG1-acids · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code Ε · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. (2,2,4-· UN "Model Regulation": TRIMETHYLHEXAN-1,6-DIAMINE,

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

CYCLOHEXANEDIMETHANAMINE), 8, II

- · Directive 2012/18/EU
- · Named dangerous substances -

ANNEX I None of the ingredients is listed.

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.06.2023 Version number 5 (replaces version 4) Revision: 06.06.2023

Trade name: Akepox 5010 Component B

· REGULATION (EU) 2019/1148

(Contd. of page 11)

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 249.0 g/l

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Department issuing SDS:
 Date of previous version:
 Laboratory
 11.05.2022

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3