

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Akepox 5030 Component A**

Article number: 11381, 12203

UFI: DDH3-003T-H00T-KJVA

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.

Storage: Store in a well-ventilated place. Keep container tightly closed.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS09

Signal word

Warning

Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane
Cyclohexanedimethanol diglycidyl ether
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Hazard statements

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 1)

· <u>Precautionary statements</u>	H317	May cause an allergic skin reaction.
	H411	Toxic to aquatic life with long lasting effects.
	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P261	Avoid breathing vapours.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P302+P352	IF ON SKIN: Wash with plenty of water.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
· <u>Additional information:</u>	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
	P337+P313	If eye irritation persists: Get medical advice/attention.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
		Contains epoxy constituents. May produce an allergic reaction.
· 2.3 Other hazards		
· <u>Results of PBT and vPvB assessment</u>		
· <u>PBT:</u> Not applicable.		
· <u>vPvB:</u> Not applicable.		

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	bis[4-(2,3-epoxypropoxy)phenyl]propane Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 14228-73-0 EINECS: 238-098-4	Cyclohexanedimethanol diglycidyl ether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<12.5%
CAS: 2530-83-8 EINECS: 219-784-2 Reg.nr.: 01-2119513212-58	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318 Aquatic Chronic 3, H412	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· <u>General information:</u>	Take affected persons out into the fresh air. Position and transport stably in side position. Immediately remove any clothing soiled by the product.
· <u>After inhalation:</u>	Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
· <u>After skin contact:</u>	If skin irritation continues, consult a doctor. Immediately wash with water and soap and rinse thoroughly.
· <u>After eye contact:</u>	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· <u>After swallowing:</u>	Rinse out mouth and then drink plenty of water.
· <u>Information for doctor:</u>	Bisphenol-A based resins: Inhalation, swallowing or dermal incorporation may cause health damage. Irritates respiratory tract, digestion system, eyes and skin: e.g., cough, dyspnea, lacrimation, burning. May cause health interferences such

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 2)

as dermal changes, renal, hepatic damage, and blood count changes. May provoke skin allergies. Sensitized users can react towards very low concentrations of Bisphenol-A-Epichlorohydrine and should avoid any further contact with this chemical.

The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight ≤ 300 . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty
Coughing
Allergic reactions

· Hazards

Danger of impaired breathing.

Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· 5.3 Advice for firefighters

· Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 3)

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Keep receptacles tightly sealed.
 - Store in cool, dry place in tightly closed receptacles.
 - Use only in well ventilated areas.
 - Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
Prevent any seepage into the ground.
 - **Information about storage in one common storage facility:** Store away from reducing agents.
 - **Further information about storage conditions:** Store receptacle in a well ventilated area.
Keep container tightly sealed.
 - **Storage class:** 12
 - **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB) 3.571 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB) 0.0893 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m³ Air (ARB)
	DNEL (Langzeit-wiederholt)	4.93 mg/m³ Air (ARB) 0.87 mg/m³ Air (BEV)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral	DNEL (Langzeit-wiederholt)	12.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	21 mg/kg bw/day (ARB) 12.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	21 mg/kg bw/day (ARB) 12.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	147 mg/m³ Air (ARB)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 4)

	DNEL (Langzeit-wiederholt)	43.5 mg/m ³ Air (BEV) 147 mg/m ³ Air (ARB) 43.5 mg/m ³ Air (BEV)
--	----------------------------	---

· PNECs**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

PNEC (wässrig)	10 mg/l (KA) 0.0006 mg/l (MW) 0.006 mg/l (SW) 0.018 mg/l (WAS)
PNEC (fest)	0.065 mg/kg Trockengew (BO) 0.034 mg/kg Trockengew (MWS) 0.341 mg/kg Trockengew (SWS)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

PNEC (wässrig)	>10 mg/l (KA) 0.1 mg/l (MW) 1 mg/l (SW) 1 mg/l (WAS)
PNEC (fest)	0.13 mg/kg Trockengew (BO) 0.79 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

· Respiratory protection:

Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Not necessary if room is well-ventilated.
Short term filter device:
Filter A/P2

· Protection of hands:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Skin protection recommendation for skin cleaning after product handling:
Kresto Classic (<http://debstoko.com>)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 5)

chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level $\leq$ 6, 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Dermatril (KCL, Art_No. 740, 741, 742)

Chloroprene rubber, CR

Camapren (KCL, Art_No. 720, 722, 726)

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye protection:**Tightly sealed goggles**· Body protection:

Protective work clothing

* **SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:Form:

Pasty

Colour:

Dark beige

· Odour:

Characteristic

· pH-value:

Not applicable

· Change in conditionMelting point/freezing point:

Undetermined.

Initial boiling point and boiling range: Undetermined.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 6)

· <u>Flash point:</u>	Not applicable.
· <u>Auto-ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product does not present an explosion hazard.
· <u>Vapour pressure at 20 °C:</u>	2 hPa
· <u>Density at 20 °C:</u>	1.56 g/cm ³
· <u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
· <u>Viscosity:</u> <u>Dynamic at 20 °C:</u> <u>Kinematic:</u>	109,000 mPas Not determined.
· <u>Solvent separation test:</u>	Not applicable
· <u>Solvent content:</u>	
<u>Solids content:</u>	44.2 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** May produce violent reactions with bases and numerous organic substances including alcohols and amines.
Strong exothermic reaction with acids.
Reacts with reducing agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	LD50	15,000 mg/kg (rat)
Dermal	LD50	23,000 mg/kg (rabbit)

14228-73-0 Cyclohexanedimethanol diglycidyl ether

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral	LD50	8,025 mg/kg (rat) (OECD 401)
	NOAEL-Werte	≥5 mg/kg (mouse) 200 mg/kg (rabbit) (OECD 414) 500 mg/kg (rat) (OECD 415)
Dermal	LD50	4,250 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>5.3 mg/l (rat) (OECD 403)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 7)

NOAEC	0.225 mg/l (rat) (OECD 412)
· Primary irritant effect:	
· Skin corrosion/irritation	Causes skin irritation.
· Serious eye damage/irritation	Causes serious eye irritation.
· Respiratory or skin sensitisation	May cause an allergic skin reaction.
· Additional toxicological information:	
· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)	
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.
· Carcinogenicity	Based on available data, the classification criteria are not met.
· Reproductive toxicity	Based on available data, the classification criteria are not met.
· STOT-single exposure	Based on available data, the classification criteria are not met.
· STOT-repeated exposure	Based on available data, the classification criteria are not met.
· Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

IC50	>100 mg/l (BES)
EC10/16h	100 mg/l (pseudomonas putida)
EC50/48h	1.8 mg/l (daphnia magna)
NOEC/21d	0.3 mg/l (daphnia magna)
EC50/72h	11 mg/l (selenastrum capricornutum)
LC50/96h	2 mg/l (Oncorhynchus mykiss)

14228-73-0 Cyclohexanedimethanol diglycidyl ether

LC0/96h	10 mg/l (piscis)
LC50/96h	13 mg/l (piscis)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

EC50/96h	350 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
	>100 mg/l (Salmo gairdneri)
EC50	119 mg/l (green alge)
IC50	255 mg/l (Scenedesmus subspicatus)
EC50/48h	324 mg/l (daphnia magna)
EC10/5h	1,500 mg/l (pseudomonas putida)
ErC50/72h	350 mg/l (Selenastrum capricornutum)
ECO/96h	44 mg/l (Cyprinus carpio)
NOEC	>100 mg/kg (Klärschlamm: Atmungs-/Vermehrungshemmung) (OECD 209)
NOEC/21d	≥100 mg/l (daphnia magna) (OECD 211)
EC50/48h	324-710 mg/l (daphnia magna) (OECD 202)
EC50/72h	255 mg/l (Scenedesmus subspicatus)
LC50/96h	55 mg/l (Cyprinus carpio) (OECD 203)
	237 mg/l (Oncorhynchus mykiss)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:

· Remark:

Toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 8)

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· 12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

· vPvB:

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods**· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information**· 14.1 UN-Number**· ADR, IMDG, IATA

UN3082

· 14.2 UN proper shipping name· ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl] propane)

· IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl] propane), MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl] propane)

· 14.3 Transport hazard class(es)· ADR· Class

9 (M6) Miscellaneous dangerous substances and articles.

· Label

9

· IMDG, IATA· Class

9 Miscellaneous dangerous substances and articles.

· Label

9

· 14.4 Packing group· ADR, IMDG, IATA

III

· 14.5 Environmental hazards:· Marine pollutant:

Yes

Symbol (fish and tree)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 9)

· <u>Special marking (ADR):</u>	Symbol (fish and tree)
· <u>Special marking (IATA):</u>	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· <u>Hazard identification number (Kemler code):</u>	90
· <u>EMS Number:</u>	F-A,S-F
· <u>Stowage Category</u>	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· <u>Transport/Additional information:</u>	
· <u>ADR</u>	
· <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>IMDG</u>	
· <u>Limited quantities (LQ)</u>	5L
· <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>UN "Model Regulation":</u>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE), 9, III

* SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· <u>Directive 2012/18/EU</u>	
· <u>Named dangerous substances - ANNEX I</u>	None of the ingredients is listed.
· <u>Seveso category</u>	E2 Hazardous to the Aquatic Environment
· <u>Qualifying quantity (tonnes) for the application of lower-tier requirements</u>	200 t
· <u>Qualifying quantity (tonnes) for the application of upper-tier requirements</u>	500 t
· <u>National regulations:</u>	
· <u>Information about limitation of use:</u>	Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed.
· <u>Waterhazard class:</u>	Water hazard class 2 (Self-assessment): hazardous for water.
· <u>VOC EU</u>	0.0 g/l
· 15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· <u>Relevant phrases</u>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.
---------------------------	--

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2021

Version number 2

Revision: 22.03.2021

Trade name: Akepox 5030 Component A

(Contd. of page 10)

· Recommended restriction of use· Department issuing SDS:· Contact:· Abbreviations and acronyms:

H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 refer to Technical Data Sheet (TDS)

Laboratory

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB