

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Universal Dilution VOC**

Article number: 90308, 90310

UFI: FWK0-H0MD-Q006-CRPA

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Thinner, Diluent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Dam. 1	H318	Causes serious eye damage.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS05 GHS07 GHS08

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 1)

· <u>Signal word</u>	Danger
· <u>Hazard-determining components of labelling:</u>	xylene (mix) butanol Solvent naphtha (petroleum), light arom.
· <u>Hazard statements</u>	H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation. H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.
· <u>Precautionary statements</u>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapours. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
· 2.3 Other hazards	
· Results of PBT and vPvB assessment	
· <u>PBT:</u>	Not applicable.
· <u>vPvB:</u>	Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119555267-33	xylene (mix) Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	25-50%
--	---	--------

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 2)

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	12.5-25%
CAS: 64742-48-9 EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412	12.5-25%
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	12.5-25%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23	butanol Flam. Liq. 3, H226 Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butanol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
Position and transport stably in side position.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- Information for doctor: Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.
Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty
Headache
Dizziness
Dizziness
Nausea

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 3)

· Hazards

Danger of impaired breathing.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures· **5.1 Extinguishing media**· Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Remove persons from danger area.

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* **SECTION 7: Handling and storage**· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 4)

- Information about fire - and explosion protection:
 - Prevent formation of aerosols.
 - Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - Use only in well ventilated areas.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Protect from heat.
- Requirements to be met by storerooms and receptacles:
 - Store in a cool location.
 - Store only in the original receptacle.
 - Prevent any seepage into the ground.
- Information about storage in one common storage facility:
 - Store away from oxidising agents.
 - Store away from foodstuffs.
- Further information about storage conditions:
 - Keep container tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Store receptacle in a well ventilated area.
- Storage class:
 - 3
- 7.3 Specific end use(s)
 - No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Additional information about design of technical facilities:
 - No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm
 Long-term value: 220 mg/m³, 50 ppm
 Sk; BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
 Long-term value: 724 mg/m³, 150 ppm

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm
 Long-term value: 154 mg/m³, 50 ppm

71-36-3 butanol

WEL Short-term value: 154 mg/m³, 50 ppm
 Sk

- DNELs

1330-20-7 xylene (mix)

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	180 mg/kg bw/day (ARB)
		108 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289 mg/m ³ Air (ARB)
		174 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	77 mg/m ³ Air (ARB)
		14.8 mg/m ³ Air (BEV)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 5)

123-86-4 n-butyl acetate

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	6 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	6 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	960 mg/m³ Air (ARB)
	DNEL (Langzeit-wiederholt)	860 mg/m³ Air (BEV)
		480 mg/m³ Air (ARB)
		102.34 mg/m³ Air (BEV)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	DNEL (Langzeit-wiederholt)	300 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	300 mg/kg bw/day (ARB)
		300 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	1,500 mg/m³ Air (ARB)
		900 mg/m³ Air (BEV)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	25 mg/kg bw/day (ARB)
		11 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	150 mg/m³ Air (ARB)
		32 mg/m³ Air (BEV)

78-83-1 butanol

Oral	DNEL (Langzeit-wiederholt)	25 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	310 mg/m³ Air (ARB)
		55 mg/m³ Air (BEV)

71-36-3 butanol

Oral	DNEL (Langzeit-wiederholt)	3.125 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	3,125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	310 mg/m³ Air (ARB)
		55 mg/m³ Air (BEV)

· PNECs**1330-20-7 xylene (mix)**

PNEC (wässrig)	6.58 mg/l (KA)
	0.327 mg/l (MW)
	0.327 mg/l (SW)
	0.327 mg/l (WAS)
PNEC (fest)	2.31 mg/kg Trockengew (BO)
	12.46 mg/kg Trockengew (MWS)
	12.46 mg/kg Trockengew (SWS)

123-86-4 n-butyl acetate

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 6)

PNEC (fest)	0.0903 mg/kg Trockengew (BO) 0.0981 mg/kg Trockengew (MWS) 0.981 mg/kg Trockengew (SWS)
-------------	---

78-83-1 butanol

PNEC (wässrig)	10 mg/l (KA) 0.04 mg/l (MW) 0.4 mg/l (SW) 11 mg/l (WAS)
PNEC (fest)	0.0699 mg/kg Trockengew (BO) 0.152 mg/kg Trockengew (MWS) 1.52 mg/kg Trockengew (SWS)

71-36-3 butanol

PNEC (wässrig)	2,476 mg/l (KA) 0.008 mg/l (MW) 0.082 mg/l (SW) 2.25 mg/l (WAS)
PNEC (fest)	0.015 mg/kg Trockengew (BO) 0.018 mg/kg Trockengew (MWS) 0.178 mg/kg Trockengew (SWS)

· Ingredients with biological limit values:**1330-20-7 xylene (mix)**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

· Personal protective equipment:
· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter AX

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 7)

After use of gloves apply skin-cleaning agents and skin cosmetics.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level $\leq$ 2, 60 min

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye protection:

Tightly sealed goggles

· Body protection:

Protective work clothing

* **SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:

Form:

Fluid

Colour:

According to product specification

· Odour:

Characteristic

· pH-value:

Not applicable

· Change in condition

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 124 °C

· Flash point:

26 °C

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 8)

· Ignition temperature:	370 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.8 Vol %
Upper:	10.4 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.85 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	20.5 mm ² /s
· Solvent content:	
Organic solvents:	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide
Possible in traces.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene (mix)

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rbt)
Inhalative	LC50/4h	29,000 mg/m ³ (rat)
	LC50/4 h	21.7 mg/l (rat)
	LC50/48h	86 mg/l (Leuciscus idus)

123-86-4 n-butyl acetate

Oral	LD50	10,800 mg/kg (rat) (OECD 423)
Dermal	LD50	>17,600 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 9)

	LC50	390 mg/m3 (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	>4.951 mg/m3 (rat) (OECD403)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	mg/l (rat)
78-83-1 butanol		
Oral	LD50	2,460 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rbt)
71-36-3 butanol		
Oral	LD50	3,430 mg/kg (rabbit) (OECD 402)
		2,292 mg/kg (rat) (OECD 401)
Dermal	LD50	3,400 mg/kg (rbt)
Inhalative	LC50/4h	17.76 mg/m3 (rat)
	LC50/4 h	8,000 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1330-20-7 xylene (mix)

EC50/24h	>175 mg/l (bacteria)
	165 mg/l (daphnia magna)
EC50	10 mg/l (bacteria)
IC50	96 mg/l (BES)
	1 mg/l (daphnia magna)
LC50	2 mg/l (piscis)
LC50/24h	32 mg/l (Iepomis macrochirus)
IC50/72h	2.2 mg/l (green alge)
	3.3 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	8 mg/l (daphnia magna)

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 10)

NOEC	0.96-1.17 mg/l (daphnia magna) >1.3 mg/l (Oncorhynchus mykiss) 0.44 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata) 2.2 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	16.9 mg/l (carassius auratus) 1.57 mg/l (Cyprinus carpio) 3.77-13.5 mg/l (piscis) 20.9 mg/l (Iepomis macrochirus) 7.6 mg/l (Oncorhynchus mykiss) 26.7 mg/l (Pimephales promelas)

123-86-4 n-butyl acetate

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (green alge)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest) 674 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.) 81 mg/l (piscis) 100 mg/l (Iepomis macrochirus) 62 mg/l (Leuciscus idus) (DIN 38412) 18 mg/l (Pimephales promelas) (OECD 203)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

EL50/48h	22-46 mg/l (daphnia magna)
EL50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	10-30 mg/l (Oncorhynchus mykiss)
NOELR/72h	<1 mg/l (Pseudokirchneriella subcapitata)

64742-95-6 Solvent naphtha (petroleum), light arom.

EC50	<10 mg/l (daphnia magna)
IC50	<10 mg/l (daphnia magna)
LC50	<10 mg/l (green alge) >1-<10 mg/l (piscis)
EL50/48h	3.2 mg/l (ceriodaphnia Dubai) 3.2 mg/l (daphnia magna)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata) 2.9 mg/l (selenastrum capricornutum)
LL50/96h	9.2 mg/l (Oncorhynchus mykiss)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	3.2 mg/l (daphnia magna)
EC50/72h	2.9 mg/l (Pseudokirchneriella subcapitata)

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 11)

LC50/96h 9.2 mg/l (Oncorhynchus mykiss)

78-83-1 butanol

EC10/18h 280 mg/l (pseudomonas putida)
 EC50/48h 1,100 mg/l (daphnia magna)
 ErC50/72h 1,799 mg/l (Pseudokirchneriella subcapitata)
 NOEC/21d 20 mg/l (daphnia magna)
 EC50/72h 2,300 mg/l (Scenedesmus subspicatus)
 LC50/96h 1,430 mg/l (Pimephales promelas)

71-36-3 butanol

EC50/96h 225 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
 EC50 4,400 mg/l (pseudomonas putida)
 IC50/72h >500 mg/l (Desmodesmus subspicatus)
 NOEC/21d 4.1 mg/l (daphnia magna)
 EC50/48h 1,328 mg/l (daphnia magna) (OECD 202)
 EC50/72h 8,500 mg/l (green alge)
 LC50/96h 1,200 mg/l (Leuciscus idus)
 1,376 mg/l (pimephales promelas) (OECD 203)
 >500 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- Ecotoxicological effects:

- Remark:

Toxic for fish

- Additional ecological information:

- General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

- **12.5 Results of PBT and vPvB assessment**

- PBT:

Not applicable.

- vPvB:

Not applicable.

- **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:

- Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

- Recommended cleansing agents:

Alcohol

SECTION 14: Transport information

- **14.1 UN-Number**

- ADR, IMDG, IATA

UN1993

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 12)

· 14.2 UN proper shipping name

· ADR

1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, BUTYL ACETATES)

· IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (XYLENES, BUTYL ACETATES)

· 14.3 Transport hazard class(es)

· ADR



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· ADR, IMDG, IATA

III

· 14.5 Environmental hazards:

· Marine pollutant:

Product contains environmentally hazardous substances:
Yes**· 14.6 Special precautions for user**

· Hazard identification number (Kemler code):

Warning: Flammable liquids.

· EMS Number:

30

· Stowage Category

F-E, S-E

A

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, BUTYL ACETATES), 3, III

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances -
ANNEX I

None of the ingredients is listed.

(Contd. on page 14)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 13)

- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- National regulations:
- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning women of child-bearing age must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC EU 848.0 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.02.2021

Version number 6

Revision: 19.02.2021

Trade name: Universal Dilution VOC

(Contd. of page 14)

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous
version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB