

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Marble Filler 1000 THIXO**
- Article number: 10417, 10422, 10424, 10426, 10428, 10430, 10431, 10432, 10435, 10438
- UFI: 1KQ2-Q0N3-000S-DWFP

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Knife filler/ Surfacers

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

- | | | |
|-------------------|-------|--|
| Flam. Liq. 3 | H226 | Flammable liquid and vapour. |
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| Repr. 2 | H361d | Suspected of damaging the unborn child. |
| STOT RE 2 | H373 | May cause damage to the hearing organs through prolonged or repeated exposure. |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

Signal word

Warning

Hazard-determining components of labelling:

styrene
titanium dioxide

Hazard statements

- H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 1)

· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe vapours.
	P280	Wear protective gloves / eye protection.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P314	Get medical advice/attention if you feel unwell.
	P403+P235	Store in a well-ventilated place. Keep cool.
· 2.3 Other hazards	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
		During processing and product hardening the network generator is released as fume. Consequently, take care for adequate air conditioning and for fume exhaustion on request.
· <u>Results of PBT and vPvB assessment</u>		
· <u>PBT:</u> Not applicable.		
· <u>vPvB:</u> Not applicable.		

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	<10%
CAS: 25013-15-4 EINECS: 246-562-2 Reg.nr.: 01-2119622074-50-0000	vinyltoluene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-xxxx	titanium dioxide Carc. 2, H351	1-5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319	<1%
CAS: 38668-48-3 EINECS: 254-075-1 Reg.nr.: 01-2119980937-17	1,1'-(p-tolylimino)dipropen-2-ol Acute Tox. 2, H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	<1%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	<1%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor: With reference to section 2 the formulation contains styrene in the indicated mass concentration range. Styrene fumes will preferably be incorporated by inhalation via respiratory tract, skin resorption is currently considered as an inferior way of incorporation. In case of inhalation styrene is absorbed in a 60-90% range. Distribution in organism occurs rapidly, the maximum blood concentration can be analyzed after one hour after incorporation. Styrene exposition affects skin, mucous membranes, and central nervous system (CNS).
Acute damages / risks to health:
In case of styrene poisoning mainly damages to and interactions with central nervous system (CNS) arise. In concentration ranges above 200 ml/m³ symptoms such as fatigue, nausea, imbalance and prolonged response times are observed.
Chronical health risks:
Effects at central and peripheral nervous system and respiratory tract are evident in literature.
Main health risks are:
- prolonged response times
- reduced cognitive performance, partial amnesia
- retardation of nervous impulse transition speed
- disturbances of pulmonary function

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness
Nausea

· Hazards

Danger of impaired breathing.
Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 3)

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

· Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Mount respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*** SECTION 7: Handling and storage****· 7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 4)

· Information about fire - and explosion protection:

Prevent formation of aerosols.

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from oxidising agents.
Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.
Keep container tightly sealed.

· Storage class:

3

· **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· Additional information about design of technical facilities:

No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm
Long-term value: 430 mg/m³, 100 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm

· DNELs

100-42-5 styrene

Oral	DNEL (Langzeit-wiederholt)	2.1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	406 mg/kg bw/day (ARB) 343 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m ³ Air (ARB) 174.25-182.75 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	85 mg/m ³ Air (ARB) 10.2 mg/m ³ Air (BEV)

25013-15-4 vinyltoluene

Oral	DNEL (Langzeit-wiederholt)	0.0833 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	5.83 mg/m ³ Air (ARB) 1.04 mg/m ³ Air (BEV)

13463-67-7 titanium dioxide

Oral	DNEL (Langzeit-wiederholt)	700 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	10 mg/m ³ Air (ARB)

64-17-5 ethanol

Oral	DNEL (Langzeit-wiederholt)	87 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	950 mg/kg bw/day (BEV)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 5)

Inhalative	DNEL (Langzeit-wiederholt)	343 mg/kg bw/day (ARB) 206 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	1,900 mg/m ³ Air (ARB) 950 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	950 mg/m ³ Air (ARB) 114 mg/m ³ Air (BEV)

38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol

Oral	DNEL (Langzeit-wiederholt)	0.3 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	0.7 mg/kg bw/day (ARB) 0.3 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2.47 mg/m ³ Air (ARB) 0.4 mg/m ³ Air (BEV)

141-78-6 ethyl acetate

Oral	DNEL (Langzeit-wiederholt)	4.5 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	63 mg/kg bw/day (ARB) 37 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,468 mg/m ³ Air (ARB) 734 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	734 mg/m ³ Air (ARB) 367 mg/m ³ Air (BEV)

· PNECs

100-42-5 styrene

PNEC (wässrig)	5 mg/l (KA)
	0.014 mg/l (MW)
	0.028 mg/l (SW)
	0.04 mg/l (WAS)
PNEC (fest)	0.2 mg/kg Trockengew (BO)
	0.307 mg/kg Trockengew (MWS)
	0.614 mg/kg Trockengew (SWS)

25013-15-4 vinyltoluene

PNEC (wässrig)	17 mg/l (KA)
	0.002 mg/l (MW)
	0.0498 mg/l (SW)
PNEC (fest)	0.0471 mg/kg Trockengew (BO)
	0.025 mg/kg Trockengew (MWS)
	1.245 mg/kg Trockengew (SWS)

13463-67-7 titanium dioxide

PNEC (wässrig)	100 mg/l (KA)
	1 mg/l (MW)
	0.127 mg/l (SW)
PNEC (fest)	100 mg/kg Trockengew (BO)
	100 mg/kg Trockengew (MWS)
	1,000 mg/kg Trockengew (SWS)

64-17-5 ethanol

PNEC (wässrig)	580 mg/l (KA)
	0.79 mg/l (MW)

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 6)

PNEC (fest)	0.96 mg/l (SW) 2.75 mg/l (WAS) 0.63 mg/kg Trockengew (BO) 0.72 mg/kg Trockengew (FUT) 2.9 mg/kg Trockengew (MWS) 3.6 mg/kg Trockengew (SWS)
38668-48-3 1,1'-(p-tolylimino)dipropen-2-ol	
PNEC (wässrig)	199.5 mg/l (KA) 0.0017 mg/l (MW) 0.017 mg/l (SW) 0.17 mg/l (WAS)
PNEC (fest)	0.005 mg/kg Trockengew (BO) 0.00782 mg/kg Trockengew (MWS) 0.0782 mg/kg Trockengew (SWS)
141-78-6 ethyl acetate	
PNEC (wässrig)	650 mg/l (KA) 0.024 mg/l (MW) 0.26 mg/l (SW) 1.65 mg/l (WAS)
PNEC (fest)	0.24 mg/kg Trockengew (BO) 0.125 mg/kg Trockengew (MWS) 1.25 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A/P2

· Protection of hands:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Skin protection recommendation for skin cleaning after product handling:
SOLOPOL (<http://www.stoko.com>)
Kresto Classic (<http://debstoko.com>)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 7)

GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level ≤ 1 , 30 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

· As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

· Not suitable are gloves made of the following materials:

Fluorocarbon rubber (Viton)

Chloroprene rubber, CR

Natural rubber, NR

Strong material gloves

Leather gloves

Nitrile rubber, NBR

· Eye protection:**Tightly sealed goggles**· Body protection:

Protective work clothing

* **SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:Form:

Pasty

Colour:

Different according to colouring

· Odour:

Characteristic

· pH-value:

Not applicable

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 8)

· <u>Change in condition</u>	
<u>Melting point/freezing point:</u>	Undetermined.
<u>Initial boiling point and boiling range:</u>	145 °C
· <u>Flash point:</u>	32 °C
· <u>Ignition temperature:</u>	480 °C
· <u>Auto-ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Explosion limits:</u>	
<u>Lower:</u>	1.2 Vol %
<u>Upper:</u>	8.9 Vol %
· <u>Vapour pressure at 20 °C:</u>	6 hPa
· <u>Density at 20 °C:</u>	1.74 g/cm ³ ([1,73 - 1,78 g/cm ³])
· <u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
· <u>Viscosity:</u>	
<u>Dynamic at 20 °C:</u>	35,000 mPas
<u>Kinematic:</u>	Not determined.
· <u>Solvent content:</u>	
<u>Organic solvents:</u>	14.3 %
<u>Solids content:</u>	82.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 - Exothermic polymerisation.
 - Reacts with peroxides and other radical forming substances.
 - Reacts with strong acids.
 - Reacts with strong alkali.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	>16,067-<128,535 mg/kg (rat)
Inhalative	LC50/4 h	82 mg/l

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 9)

100-42-5 styrene

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9.5 mg/m ³ (mouse)
		11,800 mg/m ³ (rat)
	LC50/4 h	11.8 mg/l (rat)
	NOAEC	4.34 mg/l (rat)

25013-15-4 vinyltoluene

Oral	LD50	3,375 mg/kg (rat)
	NOAEL	600 mg/kg (rat)
Dermal	LD50	4,585 mg/kg (rabbit)
Inhalative	LC50/4h	>16,891 mg/m ³ (rat)
	LC50/4 h	11 mg/l (ATE)

13463-67-7 titanium dioxide

Oral	LD50	>5,010 mg/kg (rat)
	NOAEL	24,000 mg/kg (rat)
Dermal	LD50	>10,010 mg/kg (rbt)
Inhalative	NOAEL	10 mg/m ³ (rat)
	LC50/48h	>100 mg/l (daphnia magna)

64-17-5 ethanol

Oral	LD50	10,470 mg/kg (rat) (OECD 401)
	NOAEL-Werte	>3,000 mg/kg (rat) (OECD 451)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	20,000 mg/m ³ (rat)
	LC50/4 h	120 mg/l (rat) (OECD 403)
	LC50/48h	5,012 mg/l (ceriodaphnia Dubai)
		12,340 mg/l (daphnia magna)
		8,150 mg/l (Leuciscus idus)

38668-48-3 1,1'-(p-tolylimino)dipropen-2-ol

Oral	LD50	>25-<200 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)

141-78-6 ethyl acetate

Oral	LD50	4,100 mg/kg (mouse)
		5,620 mg/kg (rat)
		4,934 mg/kg (rbt)
	NOAEL-Werte	900 mg/kg (rat)
Dermal	LD50	>18,000 mg/kg (rabbit)
Inhalative	LC50	58 mg/l (rat)
	LC50/4 h	1,600 mg/l (rat)
	LC50/1h	200 mg/l (rat)
	LC50/8h	5.86 mg/l (rat)
	LC50/48h	333 mg/l (Leuciscus idus)

- Primary irritant effect:
- Skin corrosion/irritation
- Serious eye damage/irritation
- Respiratory or skin sensitisation
- Experience with humans:

Causes skin irritation.

Causes serious eye irritation.

Based on available data, the classification criteria are not met.

After incorporation and inhalation styrene predominantly will be metabolized in the organism to mandelic and phenylglyoxylic acid and matabolites will pass through urine excretion.

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 10)

· Additional toxicological information:· Toxicokinetics, metabolism and distribution

After incorporation and inhalation styrene predominantly will be metabolized in the organism to mandelic and phenylglyoxylic acid and metabolites will pass through urine excretion.

· Acute effects (acute toxicity, irritation and corrosivity)

Styrene:

Artificial special nutrition in rat population, acute LD50 value, oral: 5000 mg/kg.
Inhalation, rat population, acute LC50 value (4h): 24 mg/l.

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Styrene

Tests for chromosome divergence:

Mouse micro-nucleus test: mutagen

Styrene:

Tests for DNA effects:

- exchange of chromatides: mutagen

- DNA chain fragmentation: mutagen

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Suspected of damaging the unborn child.

Based on available data, the classification criteria are not met.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information· **12.1 Toxicity**· Aquatic toxicity:**100-42-5 styrene**

EC50/96h	6.3 mg/l (Pseudokirchneriella subcapitata)
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)
	5.5 mg/l (Photobac. phosphoreum)
IC50/72h	4.9 mg/l (green alge)
	1.4 mg/l (selenastrum capricornutum)
IC5/8d	>200 mg/l (Scenedesmus quadricauda)
EC10/16h	72 mg/l (pseudomonas putida)
EC50/16h	>72 mg/l (pseudomonas putida)
EC50/8d	>200 mg/l (Scenedesmus quadricauda)
EC50/72u	>1-<10 mg/l (green alge)
EC20/0.5h	140 mg/l (BES) (OECD 209)
NOEC/21d	1.01 mg/l (daphnia magna)
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)
EC50/48h	0.56 mg/l (green alge)
	3.3-7.4 mg/l (daphnia magna)
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>1-<10 mg/l (piscis)
	19.03-33.53 mg/l (lem)
	3.24-4.99 mg/l (pimephales promelas)
	6.75-14.5 mg/l (Pimephales promelas)
	58.75-95.32 mg/l (poecilia reticulata)

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 11)

LC50/72h 4.9 mg/l (green alge)

25013-15-4 vinyltoluene

EC50 2.6 mg/l (Bluegill.)
 EC50/48h 1.3 mg/l (daphnia magna)
 ErC50/72h 4.3 mg/l (Pseudokirchneriella subcapitata)
 NOEC 0.563 mg/l (piscis)
 NOELR/72h 1.6 mg/l (green alge)
 NOEC/21d 0.32 mg/l (daphnia magna)
 0.563 mg/l (piscis)
 EC10 0.25 mg/l (Desmodesmus subspicatus)
 EC50/72h 0.319 mg/l (Desmodesmus subspicatus)
 5.2 mg/l (Fathead minnow)
 2.6 mg/l (senastrum capricornutum)
 LC50/96h 5.2-23.4 mg/l (piscis)
 5.2 mg/l (pimephales promelas)

13463-67-7 titanium dioxide

EC50 >1,000 mg/l (bacteria)
 EC50/48h >100 mg/l (daphnia magna)
 EC50/72h 16 mg/l (Pseudokirchneriella subcapitata)
 LC50/96h >100 mg/l (Oncorhynchus mykiss)
 >1,000 mg/l (pimephales promelas)

64-17-5 ethanol

LC50/24h 11,200 mg/l (Salmo gairdneri)
 EC50/48h 9,268-14,221 mg/l (daphnia magna)
 12,900 mg/l (Senastrum capricornutum) (OECD 201)
 EC0 6,500 mg/l (pseudomonas putida)
 5,000 mg/l (scenedesmus quadricauda)
 EC10 11.5 mg/l (CHV)
 EC50/72h 275 mg/l (CHV) (OECD 201)
 LC50/96h 13,000 mg/l (Oncorhynchus mykiss) (OECD 203)
 15,300 mg/l (pimephales promelas)

38668-48-3 1,1'-(p-tolylimino)dipropen-2-ol

EC50/48h 28.8 mg/l (daphnia magna) (OECD 202)
 EC20/0.5h >1,995 mg/l (BES) (OECD 209)
 EC50/72h 245 mg/l (Desmodesmus subspicatus) (OECD 201)
 LC50/96h 17 mg/l (Brachydanio rerio)

141-78-6 ethyl acetate

EC50/96h 220 mg/l (Pimephales promelas)
 EC10/18h 2,900 mg/l (pseudomonas putida)
 EC50/48h 610 mg/l (daphnia magna) (DIN 38412)
 5,600 mg/l (Desmodesmus subspicatus)
 IC50/48h 3,300 mg/l (Scenedesmus subspicatus)
 LC 0 29.3 mg/l (rat)
 NOELR/72h >100 mg/l (Desmodesmus subspicatus)
 NOEC/21d 2.4 mg/l (daphnia magna)
 EC10 2,900 mg/l (pseudomonas putida)

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 12)

EC50/48h	3,300 mg/l (Scenedesmus subspicatus)
LC50/96h	230 mg/l (Oncorhynchus mykiss)
	230 mg/l (Pimephales promelas)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· **Recommended cleansing agents:**

Alcohol
acetone

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN3269

· **14.2 UN proper shipping name**

· **ADR**

3269 POLYESTER RESIN KIT

· **IMDG, IATA**

POLYESTER RESIN KIT

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

3 (FT3) Flammable liquids.

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 13)

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

· Hazard identification number (Kemler code): Warning: Flammable liquids.

· EMS Number: 30

· Stowage Category: F-E,S-D

· A

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:**· ADR**

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Remarks:

Without hardener component: no dangerous goods < 450 l

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Remarks:

Without hardener component: no dangerous goods < 30 l

· IATA

· Remarks:

Without hardener component: 3/III UN 1866 Resin Solution

· UN "Model Regulation":

UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso category

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements

5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

50,000 t

· National regulations:

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· VOC EU

249.9 g/l

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 15)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 3

Revision: 04.02.2021

Trade name: Marble Filler 1000 THIXO

(Contd. of page 14)

· <u>Relevant phrases</u>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H300 Fatal if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
· <u>Recommended restriction of use</u>	refer to Technical Data Sheet (TDS)
· <u>Department issuing SDS:</u>	Laboratory
· <u>Contact:</u>	Elke Hake Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de
· <u>Abbreviations and acronyms:</u>	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 REACH directive 1907/2006/EC
· <u>Sources</u>	
· <u>* Data compared to the previous version altered.</u>	Adaptation in accordance with REACH directive 1907/2006/EC