

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Undercoating Bitumen, black, Applicator gun can**

Article number: 90011

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Protective coating
Anticorrosion additive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
(STIZ) Schweizerisches Toxikologisches Informationszentrum Zürich Tel.145
oder Tel. 044 251 51 51
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Storage:

Store in a well-ventilated place. Keep cool.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 1)

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

• Signal word

Warning

• Hazard-determining components of labelling:

Naphtha (petroleum), hydrodesulfurized heavy
 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
 Hydrocarbons, C9, aromatics

• Hazard statements

H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to the central nervous system through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 Avoid release to the environment.
 P260 Do not breathe mist/vapours/spray.
 P280 Wear protective gloves.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P314 Get medical advice/attention if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• Additional information:

• 2.3 Other hazards

EUH066 Repeated exposure may cause skin dryness or cracking.
 The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

• Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:

CAS: 8052-42-4 EINECS: 232-490-9	Asphalt substance with a Community workplace exposure limit	50-100%
-------------------------------------	--	---------

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31













Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 2)

EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H336 Aquatic Chronic 3, H412	12.5-25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H335-H336	<12.5%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-0000	Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)  Flam. Liq. 3, H226  STOT RE 1, H372; Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336	<10%
CAS: 108-32-7 EINECS: 203-572-1 Index number: 607-194-00-1	propylene carbonate  Eye Irrit. 2, H319	1-5%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures· **4.1 Description of first aid measures**· General information:

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures· **5.1 Extinguishing media**· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**· Protective equipment:

Mount respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 3)

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Mount respiratory protective device.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Prevent seepage into sewage system, workpits and cellars.
In case of seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

8052-42-4 Asphalt

WEL Short-term value: 10 mg/m³
Long-term value: 5 mg/m³

Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)

WEL Long-term value: 350 mg/m³

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 4)

· DNELs**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics**

Oral	DNEL (Langzeit-wiederholt)	125 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	208 mg/kg bw/day (ARB) 125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	871 mg/m³ Air (ARB) 185 mg/m³ Air (BEV)

Hydrocarbons, C9, aromatics

Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	25 mg/kg bw/day (ARB) 11 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	150 mg/m³ Air (ARB) 32 mg/m³ Air (BEV)

Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)

Oral	DNEL (Langzeit-wiederholt)	26 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	44 mg/kg bw/day (ARB) 26 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	570 mg/m³ Air (ARB) 570 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	330 mg/m³ Air (ARB) 71 mg/m³ Air (BEV)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Store protective clothing separately.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX

· Respiratory protection:· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 5)

- Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
Value for the permeation: Level \leq 4, 120 min
- For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR
Camatril (KCL, Art_No. 730, 731, 732, 733)
Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye protection:  Tightly sealed goggles
- Body protection: Use protective suit.

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Fluid

Colour:

Black

· Odour:

Specific type

· pH-value:

Not applicable

· Change in condition

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 110 °C

· Flash point:

24 °C

· Ignition temperature:

~490 °C

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:

0.8 Vol %

Upper:

7.0 Vol %

· Vapour pressure at 20 °C:

5 hPa

· Density at 20 °C:

1.03 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

Dynamic at 20 °C:

3500 mPas

Kinematic:

Not determined.

· Solvent content:

Organic solvents:

41.9 %

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 6)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	4951 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	4951 mg/l (rat)

Hydrocarbons, C9, aromatics

Oral	LD50	3492 mg/kg (rat) (OECD 401)
Dermal	LD50	>3160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>6193 mg/l (rat)

Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3160 mg/kg (rabbit)
		>3400 mg/kg (rat)
Inhalative	LC50/4h	>13100 mg/m3 (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to the central nervous system through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 7)

SECTION 12: Ecological information**12.1 Toxicity**Aquatic toxicity:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics**

EL50/48h	>22 - < 46 mg/l (daphnia magna)
EL50/72h	>1000 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	>10-<30 mg/l (Oncorhynchus mykiss)

Hydrocarbons, C9, aromatics

LC50	1-10 mg/l (daphnia magna)
EL50/48h	3.2 mg/l (daphnia magna) (OECD 202)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata) 2.9 mg/l (selenastrum capricornutum)
LL50/96h	9.2 mg/l (Oncorhynchus mykiss)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	7.4 mg/l (daphnia magna)

Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (2-25%)

IC50/72h	4.6-10 mg/l (green alge)
EC50/48h	43.98 mg/l (bacteria) <22 mg/l (daphnia magna)
EL50/48h	10-22 mg/l (daphnia magna)
EL50/72h	4.6-10 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	10-30 mg/l (Oncorhynchus mykiss)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.097 mg/l (daphnia magna)
LC50/96h	10-30 mg/l (piscis) <30 mg/l (Oncorhynchus mykiss)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Ecotoxicological effects:Remark:

Harmful to fish

Additional ecological information:General notes:

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

12.5 Results of PBT and vPvB assessmentPBT:

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 8)

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· ADR, ADN	Void
· IMDG, IATA	UN1300

· **14.2 UN proper shipping name**

· ADR, ADN	Void
· IMDG, IATA	TURPENTINE SUBSTITUTE

· **14.3 Transport hazard class(es)**

· ADR, ADN	
· Class	Void

· IMDG, IATA



· Class	3 Flammable liquids.
· Label	3

· **14.4 Packing group**

· ADR	Void
· IMDG	III
· IATA	II

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances:

· **14.6 Special precautions for user**

· EMS Number:	Not applicable.
· Stowage Category	F-E, S-E A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· Transport/Additional information:

· <u>IMDG</u>	
· <u>Limited quantities (LQ)</u>	5L
· <u>Excepted quantities (EQ)</u>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· <u>UN "Model Regulation":</u>	Void
---------------------------------	------

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 9)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC EU 431.9 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 18

Revision: 24.11.2015

Trade name: Undercoating Bitumen, black, Applicator gun can

(Contd. of page 10)

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

REACH directive 1907/2006/EC

• Sources

• * Data compared to the previous
version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB