

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Body Cavity Protection Spray**

Article number: 90041

UFI: 5JE4-KGF7-7C8A-KP7Y

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Anticorrosion additive
Bitumen coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960

Fax. +49(0)911-644456

e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep cool.
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS09

Signal word

Danger

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 1)

· <u>Hazard-determining components of labelling:</u>	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane Naphtha (petroleum), hydrotreated heavy Hydrocarbons, C9, aromatics Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
· <u>Hazard statements</u>	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
· <u>Precautionary statements</u>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
· <u>Additional information:</u>	Buildup of explosive mixtures possible without sufficient ventilation.
· 2.3 Other hazards	The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.
· <u>Results of PBT and vPvB assessment</u>	
· <u>PBT:</u>	Not applicable.
· <u>vPvB:</u>	Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 92128-66-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	12.5-25%

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Acute Tox. 1, H330 Press. Gas (Comp.), H280	12.5-25%
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8 Reg.nr.: 01-2119485395-27	isobutane (containing $\geq 0,1\%$ butadiene (203-450-8)) Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	1-5%
EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:
Carbon monoxide (CO)
Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

- Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 3)

- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:** Fumes can combine with air to form an explosive mixture.
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

- **DNELs**

92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

Oral	DNEL (Langzeit-wiederholt)	699 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	773 mg/kg bw/day (ARB)
		699 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2,035 mg/m ³ Air (ARB)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 4)

		608 mg/m ³ Air (BEV)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	DNEL (Langzeit-wiederholt)	125 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	208 mg/kg bw/day (ARB)
		125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	871 mg/m ³ Air (ARB)
		185 mg/m ³ Air (BEV)
Hydrocarbons, C9, aromatics		
Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	25 mg/kg bw/day (ARB)
		11 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	150 mg/m ³ Air (ARB)
		32 mg/m ³ Air (BEV)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 5)

- Material of gloves Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level ≤ 6 , 480
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye protection:  Tightly sealed goggles
- Body protection: Use protective suit.

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**Form:

Aerosol

Colour:

According to product specification

· Odour:

Specific type

· pH-value:

Not applicable

· Change in conditionMelting point/freezing point:

Undetermined.

Initial boiling point and boiling range: -44.5 °C**· Flash point:**

-97 °C

· Ignition temperature:

365 °C

· Auto-ignition temperature:

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:Lower:

0.5 Vol %

Upper:

10.9 Vol %

· Vapour pressure at 20 °C:

3,800 hPa

· Density at 20 °C:0.67 g/cm³**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 6)

· <u>Viscosity:</u>	
<u>Dynamic:</u>	Not determined.
<u>Kinematic:</u>	Not determined.
· <u>Solvent content:</u>	
<u>Organic solvents:</u>	84.3 %
<u>Solids content:</u>	5.9 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects	
· Acute toxicity	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane**

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	>2,920 mg/kg (rabbit)
	LD50	>3,160 mg/kg (rabbit) (IUCLID)
		>2,920 mg/kg (rat)
Inhalative	LC50/4 h	>25.2 mg/l (rat) (IUCLID)

106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

74-98-6 propane

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4,951 mg/l (rat)

Hydrocarbons, C9, aromatics

Oral	LD50	3,295 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>6,193 mg/l (rat)

· Primary irritant effect:	
· Skin corrosion/irritation	Causes skin irritation.
· Serious eye damage/irritation	Based on available data, the classification criteria are not met.
· Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 7)

- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

EC50/48h	3 mg/l (daphnia magna)
EL50/48h	3 mg/l (daphnia magna)
EL50/72h	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	11.4 mg/l (Oncorhynchus mykiss)
NOELR/72h	3 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.17 mg/l (daphnia magna)
LC50/96h	2.6 mg/l (piscis) (IUCLID)
LC50/72h	15.8 mg/l (Oncorhynchus mykiss)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

EL0/48h	1,000 mg/l (daphnia magna)
EL50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	>1,000 mg/l (Oncorhynchus mykiss)
NOELR/72h	100 mg/l (Pseudokirchneriella subcapitata)

Hydrocarbons, C9, aromatics

EC50/96h	9.2 mg/l (Oncorhynchus mykiss)
LC50	1-10 mg/l (daphnia magna)
ErC50/72h	0.42 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EL50/48h	3.2 mg/l (daphnia magna) (OECD 202)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata)
	2.9 mg/l (selenastrum capricornutum)
LL50/96h	9.2 mg/l (Oncorhynchus mykiss) (OECD 203)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	7.4 mg/l (daphnia magna)
EC50/72h	0.29 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:

· Remark:

Toxic for fish

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· 12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 8)

- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 02 00	wastes from MFSU of other coatings (including ceramic materials)
08 02 99	wastes not otherwise specified

- Uncleaned packaging:
- Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN-Number**
- ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

- ADR
 - IMDG
 - IATA
- 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane, Hydrocarbons, C9, aromatics), MARINE POLLUTANT AEROSOLS, flammable

14.3 Transport hazard class(es)

- ADR



- Class 2 5F Gases.
- Label 2.1

- IMDG



- Class 2.1
- Label 2.1

- IATA



- Class 2.1
- Label 2.1

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 9)

· 14.4 Packing group · <u>ADR, IMDG, IATA</u>	Void
· 14.5 Environmental hazards: · <u>Marine pollutant:</u> · <u>Special marking (ADR):</u>	Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · <u>Hazard identification number (Kemler code):</u> · <u>EMS Number:</u> · <u>Stowage Code</u> · <u>Segregation Code</u>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· <u>Transport/Additional information:</u> · <u>ADR</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u> · <u>Transport category</u> · <u>Tunnel restriction code</u>	1L Code: E0 Not permitted as Excepted Quantity 2 D
· <u>IMDG</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u>	1L Code: E0 Not permitted as Excepted Quantity
· <u>UN "Model Regulation":</u>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray

(Contd. of page 10)

· REGULATION (EC) No 1907/2006
ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.
 Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· VOC EU

582.3 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
 H224 Extremely flammable liquid and vapour.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H330 Fatal if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 refer to Technical Data Sheet (TDS)

· Recommended restriction of use

· Department issuing SDS:

Laboratory

· Contact:

Elke Hake
 Fon ++49 (0)911 64296-59
 @mail E.Hake@akemi.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 1: Flammable liquids – Category 1
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 1: Acute toxicity – Category 1
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2021

Version number 22

Revision: 28.01.2021

Trade name: Body Cavity Protection Spray· Sources

REACH directive 1907/2006/EC

(Contd. of page 11)

· * Data compared to the previous
version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB