

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **Laminating and Repair Resin**

Article number: 30231, 30227, 30228, 30234

UFI: UJD0-20J1-100K-EGJJ

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Reaction resin  
Knife filler/ Surfacer  
Polyester resin

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

Further information obtainable from:

Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.  
+44 (171) 635 91 91  
National Poison Inform. Centre  
Medical Toxicology Unit  
Avalonley Road  
London SE14 5ER

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

|                   |       |                                                                                |
|-------------------|-------|--------------------------------------------------------------------------------|
| Flam. Liq. 3      | H226  | Flammable liquid and vapour.                                                   |
| Skin Irrit. 2     | H315  | Causes skin irritation.                                                        |
| Eye Irrit. 2      | H319  | Causes serious eye irritation.                                                 |
| Skin Sens. 1      | H317  | May cause an allergic skin reaction.                                           |
| Repr. 2           | H361d | Suspected of damaging the unborn child.                                        |
| STOT RE 2         | H373  | May cause damage to the hearing organs through prolonged or repeated exposure. |
| Aquatic Chronic 2 | H411  | Toxic to aquatic life with long lasting effects.                               |

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
Storage: Store in a well-ventilated place. Keep cool.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08 GHS09

Signal word

Warning

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 1)

· Hazard-determining components of labelling:

styrene

maleic anhydride

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

H411 Toxic to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

During processing and product hardening the network generator is released as fume. Consequently, take care for adequate air conditioning and for fume exhaustion on request.

· Results of PBT and vPvB assessment

· PBT: Not applicable.· vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

|                                |                                                             |        |
|--------------------------------|-------------------------------------------------------------|--------|
| CAS: 25013-15-4                | vinyltoluene                                                | 25-50% |
| EINECS: 246-562-2              | Flam. Liq. 3, H226                                          |        |
| Reg.nr.: 01-2119622074-50-0000 | Asp. Tox. 1, H304                                           |        |
|                                | Aquatic Chronic 2, H411                                     |        |
|                                | Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 |        |

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 2)

|                                                                                               |                                                                                                                                                                                                                                       |      |
|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| CAS: 100-42-5<br>EINECS: 202-851-5<br>Index number: 601-026-00-0<br>Reg.nr.: 01-2119457861-32 | styrene<br>Flam. Liq. 3, H226<br>Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304<br>Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335<br>Aquatic Chronic 3, H412                                        | <10% |
| EC number: 911-490-9<br>Reg.nr.: 01-2119979579-10                                             | Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol<br>Eye Dam. 1, H318<br>Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317<br>Aquatic Chronic 3, H412 | <1%  |
| CAS: 108-88-3<br>EINECS: 203-625-9<br>Index number: 601-021-00-3<br>Reg.nr.: 01-2119471310-51 | toluene<br>Flam. Liq. 2, H225<br>Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304<br>Skin Irrit. 2, H315; STOT SE 3, H336<br>Aquatic Chronic 3, H412                                                                                | <1%  |
| CAS: 108-31-6<br>EINECS: 203-571-6<br>Index number: 607-096-00-9<br>Reg.nr.: 01-2119472428-31 | maleic anhydride<br>Resp. Sens. 1, H334; STOT RE 1, H372<br>Skin Corr. 1B, H314; Eye Dam. 1, H318<br>Acute Tox. 4, H302; Skin Sens. 1A, H317                                                                                          | <1%  |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.  
Position and transport stably in side position.  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm.  
Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor: With reference to section 2 the formulation contains styrene in the indicated mass concentration range. Styrene fumes will preferably be incorporated by inhalation via respiratory tract, skin resorption is currently considered as an inferior way of incorporation. In case of inhalation styrene is absorbed in a 60-90% range. Distribution in organism occurs rapidly, the maximum blood concentration can be analyzed after one hour after incorporation. Styrene exposition affects skin, mucous membranes, and central nervous system (CNS).  
Acute damages / risks to health:  
In case of styrene poisoning mainly damages to and interactions with central nervous system (CNS) arise. In concentration ranges above 200 ml/m<sup>3</sup> symptoms such as fatigue, nausea, imbalance and prolonged response times are observed.  
Chronical health risks:  
Effects at central and peripheral nervous system and respiratory tract are evident in literature.  
Main health risks are:
  - prolonged response times
  - reduced cognitive performance, partial amnesia
  - retardation of nervous impulse transition speed

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 3)

· **4.2 Most important symptoms and effects, both acute and delayed**

- disturbances of pulmonary function

· **Hazards**

Headache  
Dizziness  
Dizziness  
Nausea

Danger of impaired breathing.

Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:**

Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO<sub>x</sub>)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Mount respiratory protective device.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 4)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Use only in well ventilated areas.  
Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.  
Prevent any seepage into the ground.

**Information about storage in one common storage facility:**

Store away from oxidising agents.  
Store away from foodstuffs.

**Further information about storage conditions:**

Store receptacle in a well ventilated area.  
Keep container tightly sealed.

**Storage class:**

3

**7.3 Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Additional information about design of technical facilities:**

No further data; see item 7.

**Ingredients with limit values that require monitoring at the workplace:****100-42-5 styrene**

WEL Short-term value: 1080 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 430 mg/m<sup>3</sup>, 100 ppm

**108-88-3 toluene**

WEL Short-term value: 384 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 191 mg/m<sup>3</sup>, 50 ppm  
Sk

**108-31-6 maleic anhydride**

WEL Short-term value: 3 mg/m<sup>3</sup>  
Long-term value: 1 mg/m<sup>3</sup>  
Sen

**DNELs****25013-15-4 vinyltoluene**

|            |                            |                                                                      |
|------------|----------------------------|----------------------------------------------------------------------|
| Oral       | DNEL (Langzeit-wiederholt) | 0.0833 mg/kg bw/day (BEV)                                            |
| Inhalative | DNEL (Langzeit-wiederholt) | 5.83 mg/m <sup>3</sup> Air (ARB)<br>1.04 mg/m <sup>3</sup> Air (BEV) |

**100-42-5 styrene**

|      |                            |                        |
|------|----------------------------|------------------------|
| Oral | DNEL (Langzeit-wiederholt) | 2.1 mg/kg bw/day (BEV) |
|------|----------------------------|------------------------|

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 5)

|            |                             |                                                                                  |
|------------|-----------------------------|----------------------------------------------------------------------------------|
| Dermal     | DNEL ( Langzeit-wiederholt) | 406 mg/kg bw/day (ARB)<br>343 mg/kg bw/day (BEV)                                 |
| Inhalative | DNEL (Kurzzeit-akut)        | 289-306 mg/m <sup>3</sup> Air (ARB)<br>174.25-182.75 mg/m <sup>3</sup> Air (BEV) |
|            | DNEL (Langzeit-wiederholt)  | 85 mg/m <sup>3</sup> Air (ARB)<br>10.2 mg/m <sup>3</sup> Air (BEV)               |

**Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol**

|            |                             |                                                                    |
|------------|-----------------------------|--------------------------------------------------------------------|
| Oral       | DNEL (Langzeit-wiederholt)  | 0.83 mg/kg bw/day (BEV)                                            |
| Dermal     | DNEL ( Langzeit-wiederholt) | 1.4 mg/kg bw/day (ARB)<br>0.83 mg/kg bw/day (BEV)                  |
| Inhalative | DNEL (Langzeit-wiederholt)  | 9.8 mg/m <sup>3</sup> Air (ARB)<br>2.9 mg/m <sup>3</sup> Air (BEV) |

**108-88-3 toluene**

|            |                             |                                                                     |
|------------|-----------------------------|---------------------------------------------------------------------|
| Oral       | DNEL (Langzeit-wiederholt)  | 8.13 mg/kg bw/day (BEV)                                             |
| Dermal     | DNEL ( Langzeit-wiederholt) | 384 mg/kg bw/day (ARB)<br>226 mg/kg bw/day (BEV)                    |
| Inhalative | DNEL (Kurzzeit-akut)        | 384 mg/m <sup>3</sup> Air (ARB)<br>226 mg/m <sup>3</sup> Air (BEV)  |
|            | DNEL (Langzeit-wiederholt)  | 192 mg/m <sup>3</sup> Air (ARB)<br>56.5 mg/m <sup>3</sup> Air (BEV) |

**108-31-6 maleic anhydride**

|            |                             |                                                                          |
|------------|-----------------------------|--------------------------------------------------------------------------|
| Oral       | DNEL (Langzeit-wiederholt)  | 0.06 mg/kg bw/day (BEV)                                                  |
| Dermal     | DNEL (Kurzzeit-akut)        | 0.04 mg/kg bw/day (ARB)                                                  |
|            | DNEL ( Langzeit-wiederholt) | 0.2 mg/kg bw/day (ARB)<br>0.1 mg/kg bw/day (BEV)                         |
| Inhalative | DNEL (Kurzzeit-akut)        | 0.95 mg/m <sup>3</sup> Air (ARB)                                         |
|            | DNEL (Langzeit-wiederholt)  | 0.19-0.4 mg/m <sup>3</sup> Air (ARB)<br>0.08 mg/m <sup>3</sup> Air (BEV) |

**· PNECs**
**25013-15-4 vinyltoluene**

|                |                                                                                              |
|----------------|----------------------------------------------------------------------------------------------|
| PNEC (wässrig) | 17 mg/l (KA)<br>0.002 mg/l (MW)<br>0.0498 mg/l (SW)                                          |
| PNEC (fest)    | 0.0471 mg/kg Trockengew (BO)<br>0.025 mg/kg Trockengew (MWS)<br>1.245 mg/kg Trockengew (SWS) |

**100-42-5 styrene**

|                |                                                                                           |
|----------------|-------------------------------------------------------------------------------------------|
| PNEC (wässrig) | 5 mg/l (KA)<br>0.014 mg/l (MW)<br>0.028 mg/l (SW)<br>0.04 mg/l (WAS)                      |
| PNEC (fest)    | 0.2 mg/kg Trockengew (BO)<br>0.307 mg/kg Trockengew (MWS)<br>0.614 mg/kg Trockengew (SWS) |

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 6)

**Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol**

|                |                                                                                         |
|----------------|-----------------------------------------------------------------------------------------|
| PNEC (wässrig) | 10 mg/l (KA)<br>0.005 mg/l (MW)<br>0.048 mg/l (SW)                                      |
| PNEC (fest)    | 0.21 mg/kg Trockengew (BO)<br>0.12 mg/kg Trockengew (MWS)<br>1.2 mg/kg Trockengew (SWS) |

**108-88-3 toluene**

|                |                                                                                            |
|----------------|--------------------------------------------------------------------------------------------|
| PNEC (wässrig) | 13.61 mg/l (KA)<br>0.68 mg/l (MW)<br>0.68 mg/l (SW)<br>0.68 mg/l (WAS)                     |
| PNEC (fest)    | 2.89 mg/kg Trockengew (BO)<br>16.39 mg/kg Trockengew (MWS)<br>16.39 mg/kg Trockengew (SWS) |

**108-31-6 maleic anhydride**

|                |                                                                                               |
|----------------|-----------------------------------------------------------------------------------------------|
| PNEC (wässrig) | 44.6 mg/l (KA)<br>0.00446 mg/l (MW)<br>0.0446 mg/l (SW)<br>0.4281 mg/l (WAS)                  |
| PNEC (fest)    | 0.0415 mg/kg Trockengew (BO)<br>0.0334 mg/kg Trockengew (MWS)<br>0.334 mg/kg Trockengew (SWS) |

Additional information:

The lists valid during the making were used as basis.

**8.2 Exposure controls**

- Personal protective equipment:
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.  
 Use skin protection cream for skin protection.  
 Clean skin thoroughly immediately after handling the product.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.  
 Suitable respiratory protective device recommended.  
 Short term filter device:  
 Filter AX  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
 Preventive skin protection by use of skin-protecting agents is recommended.  
 After use of gloves apply skin-cleaning agents and skin cosmetics.

Respiratory protection:
Protection of hands:

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type.

(Contd. on page 8)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name: Laminating and Repair Resin**

(Contd. of page 7)

The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level  $\leq 2$ , 30 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art\_No. 897, 898)

· As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR

· Not suitable are gloves made of the following materials:

Chloroprene rubber, CR

Leather gloves

Strong material gloves

· Eye protection:

Tightly sealed goggles

· Body protection:

Protective work clothing

**SECTION 9: Physical and chemical properties**· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:Form:

Fluid

Colour:

Yellow

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not applicable

· Change in conditionMelting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 145 °C· Flash point:

32 °C

· Ignition temperature:

480 °C

· Decomposition temperature:

Not determined.

(Contd. on page 9)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 8)

|                                                  |                                                                                             |
|--------------------------------------------------|---------------------------------------------------------------------------------------------|
| · <u>Auto-ignition temperature:</u>              | Product is not selfigniting.                                                                |
| · <u>Explosive properties:</u>                   | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <u>Explosion limits:</u>                       |                                                                                             |
| Lower:                                           | 1.2 Vol %                                                                                   |
| Upper:                                           | 8.9 Vol %                                                                                   |
| · <u>Vapour pressure at 20 °C:</u>               | 6 hPa                                                                                       |
| · <u>Density at 20 °C:</u>                       | 1.13 g/cm <sup>3</sup>                                                                      |
| · <u>Relative density</u>                        | Not determined.                                                                             |
| · <u>Vapour density</u>                          | Not determined.                                                                             |
| · <u>Evaporation rate</u>                        | Not determined.                                                                             |
| · <u>Solubility in / Miscibility with water:</u> | Not miscible or difficult to mix.                                                           |
| · <u>Partition coefficient: n-octanol/water:</u> | Not determined.                                                                             |
| · <u>Viscosity:</u>                              |                                                                                             |
| Dynamic:                                         | Not determined.                                                                             |
| Kinematic at 20 °C:                              | 210 s (DIN 53211/4)                                                                         |
| · <u>Solvent content:</u>                        |                                                                                             |
| Organic solvents:                                | 40.5 %                                                                                      |
| Solids content:                                  | 65.0 %                                                                                      |
| · <b>9.2 Other information</b>                   | No further relevant information available.                                                  |

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Exothermic polymerisation.  
Reacts with peroxides and other radical forming substances.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Inhalative LC50/4 h 27.6 mg/l

**25013-15-4 vinyltoluene**

|            |         |                                 |
|------------|---------|---------------------------------|
| Oral       | LD50    | 3,375 mg/kg (rat)               |
|            | NOAEL   | 600 mg/kg (rat)                 |
| Dermal     | LD50    | 4,585 mg/kg (rabbit)            |
| Inhalative | LC50/4h | >16,891 mg/m <sup>3</sup> (rat) |

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 9)

|                                                                                                                                |          |                                              |
|--------------------------------------------------------------------------------------------------------------------------------|----------|----------------------------------------------|
|                                                                                                                                | LC50/4 h | 11 mg/l (ATE)                                |
| <b>100-42-5 styrene</b>                                                                                                        |          |                                              |
| Oral                                                                                                                           | LD50     | >2,000 mg/kg (rat)                           |
| Dermal                                                                                                                         | LD50     | >2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402) |
| Inhalative                                                                                                                     | LC50/4h  | 9.5 mg/m <sup>3</sup> (mouse)                |
|                                                                                                                                |          | 11,800 mg/m <sup>3</sup> (rat)               |
|                                                                                                                                | LC50/4 h | 11.8 mg/l (rat)                              |
|                                                                                                                                | NOAEC    | 4.34 mg/l (rat)                              |
| <b>Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol</b> |          |                                              |
| Oral                                                                                                                           | LD50     | 619 mg/kg (rat)                              |
| Dermal                                                                                                                         | LD50     | >2,000 mg/kg (rat)                           |
| <b>108-88-3 toluene</b>                                                                                                        |          |                                              |
| Oral                                                                                                                           | LD50     | 5,580 mg/kg (rat)                            |
| Dermal                                                                                                                         | LD50     | 12,124 mg/kg (rabbit)                        |
| Inhalative                                                                                                                     | LC50/4 h | 5,320 mg/l (mus)                             |
|                                                                                                                                |          | 25.7-30 mg/l (rat)                           |
| <b>108-31-6 maleic anhydride</b>                                                                                               |          |                                              |
| Oral                                                                                                                           | LD50     | 1,090-2,620 mg/kg (rabbit)                   |
|                                                                                                                                |          | 400-480 mg/kg (rat)                          |
| Dermal                                                                                                                         | LD50     | 2,620 mg/kg (rabbit)                         |
| Inhalative                                                                                                                     | LC50/1h  | >4.35 mg/l (rat)                             |
|                                                                                                                                | LC50/48h | 138 mg/l (lem)                               |

· Primary irritant effect:

- Skin corrosion/irritation
- Serious eye damage/irritation
- Respiratory or skin sensitisation
- Experience with humans:

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

After incorporation and inhalation styrene predominantly will be metabolized in the organism to mandelic and phenylglyoxylic acid and metabolites will pass through urine excretion.

· Additional toxicological information:

- Toxicokinetics, metabolism and distribution

After incorporation and inhalation styrene predominantly will be metabolized in the organism to mandelic and phenylglyoxylic acid and metabolites will pass through urine excretion.

- Acute effects (acute toxicity, irritation and corrosivity)

Styrene:

Artificial special nutrition in rat population, acute LD50 value, oral: 5000 mg/kg.  
Inhalation, rat population, acute LC50 value (4h): 24 mg/l.

- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Styrene

Tests for chromosome divergence:

Mouse micro-nucleus test: mutagen

Styrene:

Tests for DNA effects:

- exchange of chromatides: mutagen

- DNA chain fragmentation: mutagen

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Suspected of damaging the unborn child.

Based on available data, the classification criteria are not met.

May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 11)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

· Aspiration hazard

Based on available data, the classification criteria are not met.

(Contd. of page 10)

**SECTION 12: Ecological information****· 12.1 Toxicity**

· Aquatic toxicity:

**25013-15-4 vinyltoluene**

|           |                                            |
|-----------|--------------------------------------------|
| EC50      | 2.6 mg/l (Bluegill.)                       |
| EC50/48h  | 1.3 mg/l (daphnia magna)                   |
| ErC50/72h | 4.3 mg/l (Pseudokirchneriella subcapitata) |
| NOEC      | 0.563 mg/l (piscis)                        |
| NOELR/72h | 1.6 mg/l (green alge)                      |
| NOEC/21d  | 0.32 mg/l (daphnia magna)                  |
|           | 0.563 mg/l (piscis)                        |
| EC10      | 0.25 mg/l (Desmodesmus subspicatus)        |
| EC50/72h  | 0.319 mg/l (Desmodesmus subspicatus)       |
|           | 5.2 mg/l (Fathead minnow)                  |
|           | 2.6 mg/l (selenastrum capricornutum)       |
| LC50/96h  | 5.2-23.4 mg/l (piscis)                     |
|           | 5.2 mg/l (pimephales promelas)             |

**100-42-5 styrene**

|           |                                                                |
|-----------|----------------------------------------------------------------|
| EC50/96h  | 6.3 mg/l (Pseudokirchneriella subcapitata)                     |
| EC50      | 500 mg/l (BES) (ISO Vorschrift 8192-1986 E)                    |
|           | 5.5 mg/l (Photobac. phosphoreum)                               |
| IC50/72h  | 4.9 mg/l (green alge)                                          |
|           | 1.4 mg/l (selenastrum capricornutum)                           |
| IC5/8d    | >200 mg/l (Scenedesmus quadricauda)                            |
| EC10/16h  | 72 mg/l (pseudomonas putida)                                   |
| EC50/16h  | >72 mg/l (pseudomonas putida)                                  |
| EC50/8d   | >200 mg/l (Scenedesmus quadricauda)                            |
| EC50/72u  | >1-<10 mg/l (green alge)                                       |
| EC20/0.5h | 140 mg/l (BES) (OECD 209)                                      |
| NOEC/21d  | 1.01 mg/l (daphnia magna)                                      |
| EC10      | 0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050) |
| EC50/48h  | 0.56 mg/l (green alge)                                         |
|           | 3.3-7.4 mg/l (daphnia magna)                                   |
| EC50/72h  | 0.46-4.3 mg/l (Pseudokirchneriella subcapitata)                |
| LC50/96h  | >1-<10 mg/l (piscis)                                           |
|           | 19.03-33.53 mg/l (lem)                                         |
|           | 3.24-4.99 mg/l (pimephales promelas)                           |
|           | 6.75-14.5 mg/l (Pimephales promelas)                           |
|           | 58.75-95.32 mg/l (poecilia reticulata)                         |
| LC50/72h  | 4.9 mg/l (green alge)                                          |

**Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-ethanol**

|          |                                             |
|----------|---------------------------------------------|
| EC50/48h | 48 mg/l (daphnia magna)                     |
| EC50/72h | >100 mg/l (Pseudokirchneriella subcapitata) |

(Contd. on page 12)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name: Laminating and Repair Resin**

(Contd. of page 11)

|                                  |                                                         |
|----------------------------------|---------------------------------------------------------|
| LC50/96h                         | >100 mg/l (Cyprinus carpio)                             |
| <b>108-88-3 toluene</b>          |                                                         |
| EC50/24h                         | 84 mg/l (BES)                                           |
| EC50/96h                         | >433 mg/l (Pseudokirchneriella subcapitata)             |
| IC50/72h                         | 12 mg/l (Pseudokirchneriella subcapitata) (lit.)        |
|                                  | 12 mg/l (Selenastrum capricornutum) (lit.)              |
| EC50/48h                         | 5.46-11.5 mg/l (daphnia magna) (lit.)                   |
| NOEC                             | 0.74 mg/kg (daphnia magna)                              |
| EC50/48h                         | 3.78 mg/l (daphnia magna)                               |
| EC50/72h                         | 10 mg/l (green alge)                                    |
|                                  | 12.5 mg/l (Pseudokirchneriella subcapitata)             |
| LC50/96h                         | 5.5 mg/l (piscis)                                       |
|                                  | 11-15 mg/l (lem)                                        |
|                                  | 5.8-17 mg/l (Oncorhynchus mykiss) (lit.)                |
|                                  | 54 mg/l (Oryzias latipes)                               |
|                                  | 12.6-19.05 mg/l (pimephales promelas)                   |
|                                  | 7-28.2 mg/l (poecilia reticulata)                       |
| <b>108-31-6 maleic anhydride</b> |                                                         |
| EC50/24h                         | 316-330 mg/l (daphnia magna)                            |
| EC50                             | 77 mg/l (daphnia magna)                                 |
| EC10/18h                         | 44.6 mg/l (pseudomonas putida)                          |
| EC50/48h                         | 42.81 mg/l (daphnia magna)                              |
| ErC50/72h                        | 74.35 mg/l (Pseudokirchneriella subcapitata) (OECD 202) |
| NOELR/72h                        | 150 mg/l (Pseudokirchneriella subcapitata)              |
| NOEC/21d                         | 10 mg/l (daphnia magna)                                 |
| EC50/72h                         | 29 mg/l (Desmodesmus subspicatus)                       |
|                                  | 74.32 mg/l (Pseudokirchneriella subcapitata)            |
|                                  | >150 mg/l (Selenastrum capricornutum)                   |
| LC50/96h                         | 75 mg/l (Iepomis macrochirus)                           |
|                                  | 75 mg/l (Oncorhynchus mykiss)                           |

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

\* **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 13)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 12)

· Recommended cleansing agents: Alcohol  
acetone

## SECTION 14: Transport information

· **14.1 UN-Number**  
· ADR, IMDG, IATA

UN3269

· **14.2 UN proper shipping name**

· ADR

3269 POLYESTER RESIN KIT, ENVIRONMENTALLY HAZARDOUS

· IMDG

POLYESTER RESIN KIT (VINYL TOLUENES, STABILIZED), MARINE POLLUTANT

· IATA

POLYESTER RESIN KIT

· **14.3 Transport hazard class(es)**

· ADR

· Class  
· Label

3 (F3) Flammable liquids.  
3

· IMDG

· Class  
· Label

3 Flammable liquids.  
3

· IATA

· Class  
· Label

3 Flammable liquids.  
3

· **14.4 Packing group**

· ADR, IMDG, IATA

III

· **14.5 Environmental hazards:**

· Marine pollutant:

No

· Special marking (ADR):

Symbol (fish and tree)  
Symbol (fish and tree)

· **14.6 Special precautions for user**

· Hazard identification number (Kemler code):

Warning: Flammable liquids.

· EMS Number:

-

· Stowage CategoryF-E, S-D  
A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 14)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name:** Laminating and Repair Resin

(Contd. of page 13)

· Transport/Additional information:· ADR· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· IMDG· Limited quantities (LQ)· Excepted quantities (EQ)

5L

Code: See SP340

· UN "Model Regulation":UN 3269 POLYESTER RESIN KIT, 3, III,  
ENVIRONMENTALLY HAZARDOUS

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso categoryE2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS· Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

· National regulations:· Information about limitation of use:Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· VOC EU

458.2 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 15)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 04.02.2021

Version number 13

Revision: 04.02.2021

**Trade name: Laminating and Repair Resin**

(Contd. of page 14)

· Recommended restriction of use· Department issuing SDS:· Contact:· Abbreviations and acronyms:

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

refer to Technical Data Sheet (TDS)

Laboratory

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

REACH directive 1907/2006/EC

· Sources· \* Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC