

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Car Body Sealant**

Article number: 90603, 90607

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep cool.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5












Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 1)

· <u>Signal word</u>	Danger
· <u>Hazard-determining components of labelling:</u>	Naphtha (petroleum), hydrotreated light Naphtha (petroleum), hydrotreated heavy Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane
· <u>Hazard statements</u>	H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
· <u>Precautionary statements</u>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243 Take action to prevent static discharges. P261 Avoid breathing vapours. P273 Avoid release to the environment. P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of water. P312 Call a POISON CENTER/doctor if you feel unwell. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
· <u>Additional information:</u>	EUH066 Repeated exposure may cause skin dryness or cracking.
· 2.3 Other hazards	
· <u>Results of PBT and vPvB assessment</u>	
· <u>PBT:</u>	Not applicable.
· <u>vPvB:</u>	Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 64742-49-0 EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Naphtha (petroleum), hydrotreated light  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336	<12.5%
CAS: 64742-48-9 EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Naphtha (petroleum), hydrotreated heavy  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H336 Aquatic Chronic 3, H412	<12.5%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 2)

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
 - Breathing difficulty
 - Headache
 - Dizziness
 - Dizziness
 - Nausea
- Information for doctor: Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

* **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - In case of fire, the following can be released:
 - Carbon monoxide (CO)
 - Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- Protective equipment: Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

* **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Keep away from ignition sources.
 - Ensure adequate ventilation
 - Product forms slippery surface when combined with water.
- **6.2 Environmental precautions:** Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.
 Keep ignition sources away - Do not smoke.
 Flammable gas-air mixtures may form in empty receptacles.
 Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.
 Store in a cool location.
 Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**Additional information about design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs**64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	DNEL (Langzeit-wiederholt)	699 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	773 mg/kg bw/day (ARB)
		699 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2,035 mg/m³ Air (ARB)
		608 mg/m³ Air (BEV)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	DNEL (Langzeit-wiederholt)	300 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	300 mg/kg bw/day (ARB)
		300 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	1,500 mg/m³ Air (ARB)
		900 mg/m³ Air (BEV)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

Oral	DNEL (Langzeit-wiederholt)	699 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	773 mg/kg bw/day (ARB)
		699 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2,035 mg/m³ Air (ARB)
		608 mg/m³ Air (BEV)

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 4)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter AX

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level ≤ 6, 480 min

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, Art_No. 730, 731, 732, 733)

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 5)

- Camatril (KCL, 730, 731, 732, 733)
Neoprene gloves
- Not suitable are gloves made of the following materials:
Leather gloves
Strong material gloves
- Eye protection:
 Tightly sealed goggles
- Body protection:
Protective work clothing

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

Form: Highly viscous
Colour: Various colours
Odour: Specific type

· pH-value: Not applicable

· Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: Undetermined.

· Flash point: -8 °C

· Ignition temperature: 240 °C

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.6 Vol %
Upper: 7 Vol %

· Vapour pressure at 20 °C: 1 hPa

· Density at 20 °C: 1.13 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

Dynamic: Not determined.
Kinematic at 40 °C: 2,100 mm²/s

· Solvent content:

Organic solvents: 30.0 %

Solids content: 69.5 %

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity**· 10.1 Reactivity**

No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with strong oxidising agents.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 6)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Flammable gases/vapours

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,800 mg/kg (rabbit)
	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	>4.951 mg/m3 (rat) (OECD403)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	>2,920 mg/kg (rabbit)
	LD50	>3,160 mg/kg (rabbit) (IUCLID)
		>2,920 mg/kg (rat)
Inhalative	LC50/4 h	>25.2 mg/l (rat) (IUCLID)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity:

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50/48h	3 mg/l (daphnia magna)
EL50/72h	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	>13.4 mg/l (Oncorhynchus mykiss)
NOELR/72h	10 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.17 mg/l (daphnia magna)
LC50/96h	<10 mg/l (daphnia magna)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

EL50/48h	22-46 mg/l (daphnia magna)
----------	----------------------------

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 7)

EL50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	10-30 mg/l (Oncorhynchus mykiss)
NOELR/72h	<1 mg/l (Pseudokirchneriella subcapitata)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

EC50/48h	3 mg/l (daphnia magna)
EL50/48h	3 mg/l (daphnia magna)
EL50/72h	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	11.4 mg/l (Oncorhynchus mykiss)
NOELR/72h	3 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.17 mg/l (daphnia magna)
LC50/96h	2.6 mg/l (piscis) (IUCLID)
LC50/72h	15.8 mg/l (Oncorhynchus mykiss)

• **12.2 Persistence and degradability**

No further relevant information available.

• **12.3 Bioaccumulative potential**

No further relevant information available.

• **12.4 Mobility in soil**

No further relevant information available.

• Ecotoxicological effects:

• Remark:

Harmful to fish

• Additional ecological information:

• General notes:

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

• **12.5 Results of PBT and vPvB assessment**

• PBT:

Not applicable.

• vPvB:

Not applicable.

• **12.6 Other adverse effects**

No further relevant information available.

* **SECTION 13: Disposal considerations**

• **13.1 Waste treatment methods**

• Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

• Uncleaned packaging:

• Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

* **SECTION 14: Transport information**

• **14.1 UN-Number**

• ADR, IMDG, IATA

UN1133

• **14.2 UN proper shipping name**

• ADR

1133 ADHESIVES

• IMDG, IATA

ADHESIVES

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 8)

14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.
 · Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
 · Label 3

14.4 Packing group

· ADR, IMDG, IATA III

14.5 Environmental hazards:

· Marine pollutant: No

14.6 Special precautions for user

Warning: Flammable liquids.
 · Danger code (Kemler): 33
 · EMS Number: F-E,S-D
 · Stowage Category A

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR
 · Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 · Transport category 3
 · Tunnel restriction code D/E

· IMDG
 · Limited quantities (LQ) 5L
 · Excepted quantities (EQ) Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU
 · Named dangerous substances - ANNEX I None of the ingredients is listed.
 · Seveso category P5c FLAMMABLE LIQUIDS

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.03.2019

Version number 5

Revision: 15.03.2019

Trade name: Car Body Sealant

(Contd. of page 9)

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- VOC EU 339.0 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
REACH directive 1907/2006/EC
- Sources
- * Data compared to the previous version altered. Adaptation in accordance with REACH directive 1907/2006/EC