

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Wheel Rim Silver**

Article number: 90003

UFI: 5PH0-C0P2-R00A-5VHN

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Lacquer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word

Danger

Hazard-determining components of labelling:

acetone

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 1)

P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P280 Wear protective gloves / eye protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 Buildup of explosive mixtures possible without sufficient ventilation.

· Additional information:· **2.3 Other hazards**

· Results of PBT and vPvB assessment

· PBT: Not applicable.· vPvB: Not applicable.**SECTION 3: Composition/information on ingredients**· **3.2 Chemical characterisation: Mixtures**· Description: Mixture: consisting of the following components.· Dangerous components:

| | | |
|---|--|----------|
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49 | acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 | 25-50% |
| CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37 | dimethyl ether Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280 | 12.5-25% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1A, H220 Acute Tox. 1, H330 Press. Gas (Comp.), H280 | <12.5% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32 | butane, pure Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280 | <12.5% |
| CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 | <10% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280 | 1-5% |
| CAS: 9004-70-0 Index number: 603-037-00-6 | nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228 | 1-5% |

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 2)

| | | |
|--|--|------|
| CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45 | aluminium powder (stabilised) Flam. Sol. 1, H228; Water-react. 3, H261 | 1-5% |
| EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32; 01-2119486136-34 | reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 1-5% |
| CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43 | ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319 | 1-5% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor: Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.
Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness
Gastric or intestinal disorders
Nausea
Coughing
Profuse sweating
Danger of impaired breathing.

· Hazards

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 3)

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:
Carbon monoxide (CO)
During heating or in case of fire poisonous gases are produced.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Mount respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Not required.

· Further information about storage conditions:

Protect from frost.
Keep container tightly sealed.

· **7.3 Specific end use(s)**

No further relevant information available.

*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· Additional information about design of technical facilities:

No further data; see item 7.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 4)

· Ingredients with limit values that require monitoring at the workplace:**67-64-1 acetone**

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

· DNELs**67-64-1 acetone**

| | | |
|------------|----------------------------|-----------------------------------|
| Oral | DNEL (Langzeit-wiederholt) | 62 mg/kg bw/day (BEV) |
| Dermal | DNEL (Langzeit-wiederholt) | 186 mg/kg bw/day (ARB) |
| Inhalative | | 62 mg/kg bw/day (BEV) |
| | DNEL (Kurzzeit-akut) | 2,420 mg/m ³ Air (ARB) |
| | DNEL (Langzeit-wiederholt) | 1,210 mg/m ³ Air (ARB) |
| | | 200 mg/m ³ Air (BEV) |

115-10-6 dimethyl ether

| | | |
|------------|----------------------------|-----------------------------------|
| Inhalative | DNEL (Langzeit-wiederholt) | 1,894 mg/m ³ Air (ARB) |
| | | 471 mg/m ³ Air (BEV) |

123-86-4 n-butyl acetate

| | | |
|------------|----------------------------|------------------------------------|
| Oral | DNEL (Kurzzeit-akut) | 2 mg/kg bw/day (BEV) |
| | DNEL (Langzeit-wiederholt) | 2 mg/kg bw/day (BEV) |
| Dermal | DNEL (Kurzzeit-akut) | 11 mg/kg bw/day (ARB) |
| | | 6 mg/kg bw/day (BEV) |
| Inhalative | DNEL (Langzeit-wiederholt) | 11 mg/kg bw/day (ARB) |
| | | 6 mg/kg bw/day (BEV) |
| | DNEL (Kurzzeit-akut) | 960 mg/m ³ Air (ARB) |
| | | 860 mg/m ³ Air (BEV) |
| | DNEL (Langzeit-wiederholt) | 480 mg/m ³ Air (ARB) |
| | | 102.34 mg/m ³ Air (BEV) |

reaction mass of ethylbenzole and xylene

| | | |
|------------|----------------------------|---------------------------------------|
| Oral | DNEL (Langzeit-wiederholt) | 1.6 mg/kg bw/day (BEV) |
| Dermal | DNEL (Langzeit-wiederholt) | 180 mg/kg bw/day (ARB) |
| | | 108 mg/kg bw/day (BEV) |
| Inhalative | DNEL (Kurzzeit-akut) | 289-442 mg/m ³ Air (ARB) |
| | | 260 mg/m ³ Air (BEV) |
| | DNEL (Langzeit-wiederholt) | 77 mg/m ³ Air (ARB) |
| | | 14.8-65.3 mg/m ³ Air (BEV) |

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 5)

64-17-5 ethanol

| | | |
|------------|-----------------------------|------------------------|
| Oral | DNEL (Langzeit-wiederholt) | 87 mg/kg bw/day (BEV) |
| Dermal | DNEL (Kurzzeit-akut) | 950 mg/kg bw/day (BEV) |
| | DNEL (Langzeit-wiederholt) | 343 mg/kg bw/day (ARB) |
| Inhalative | | 206 mg/kg bw/day (BEV) |
| | DNEL (Kurzzeit-akut) | 1,900 mg/m³ Air (ARB) |
| | | 950 mg/m³ Air (BEV) |
| | DNEL (Langzeit-wiederholt) | 950 mg/m³ Air (ARB) |
| | | 114 mg/m³ Air (BEV) |

· PNECs

67-64-1 acetone

| | |
|----------------|-----------------------------|
| PNEC (wässrig) | 100 mg/l (KA) |
| | 1.06 mg/l (MW) |
| | 10.6 mg/l (SW) |
| | 21 mg/l (WAS) |
| PNEC (fest) | 29.5 mg/kg Trockengew (BO) |
| | 3.04 mg/kg Trockengew (MWS) |
| | 30.4 mg/kg Trockengew (SWS) |

115-10-6 dimethyl ether

| | |
|----------------|-------------------------------|
| PNEC (wässrig) | 160 mg/l (KA) |
| | 0.016 mg/l (MW) |
| | 0.155 mg/l (SW) |
| PNEC (fest) | 0.045 mg/kg Trockengew (BO) |
| | 0.0681 mg/kg Trockengew (MWS) |
| | 0.681 mg/kg Trockengew (SWS) |

123-86-4 n-butyl acetate

| | |
|----------------|-------------------------------|
| PNEC (wässrig) | 35.6 mg/l (KA) |
| | 0.018 mg/l (MW) |
| | 0.18 mg/l (SW) |
| | 0.36 mg/l (WAS) |
| PNEC (fest) | 0.0903 mg/kg Trockengew (BO) |
| | 0.0981 mg/kg Trockengew (MWS) |
| | 0.981 mg/kg Trockengew (SWS) |

reaction mass of ethylbenzole and xylol

| | |
|----------------|------------------------------|
| PNEC (wässrig) | 6.58 mg/l (KA) |
| | 0.327 mg/l (MW) |
| | 0.327 mg/l (SW) |
| PNEC (fest) | 2.31 mg/kg Trockengew (BO) |
| | 12.46 mg/kg Trockengew (MWS) |
| | 12.46 mg/kg Trockengew (SWS) |

64-17-5 ethanol

| | |
|----------------|----------------------------|
| PNEC (wässrig) | 580 mg/l (KA) |
| | 0.79 mg/l (MW) |
| | 0.96 mg/l (SW) |
| | 2.75 mg/l (WAS) |
| PNEC (fest) | 0.63 mg/kg Trockengew (BO) |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 6)

0.72 mg/kg Trockengew (FUT)

2.9 mg/kg Trockengew (MWS)

3.6 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level \leq 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 · For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 7)

- As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR
- Not suitable are gloves made of the following materials: Nitrile rubber, NBR
Butoject (KCL, Art_No. 897, 898)
Butyl rubber, BR
- Eye protection: Natural rubber, NR
Leather gloves
Strong material gloves
- Body protection:  Tightly sealed goggles
Light weight protective clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

- Form: Aerosol
- Colour: Silver-coloured
- Odour: Specific type
- Odour threshold: Not determined.

- pH-value: Not applicable

· Change in condition

- Melting point/freezing point: Undetermined.
- Initial boiling point and boiling range: Not applicable, as aerosol.

- Flash point: Not applicable, as aerosol.

- Flammability (solid, gas): Not applicable.

- Ignition temperature: 240 °C

- Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

- Lower: 1.7 Vol %
- Upper: 26.2 Vol %

- Vapour pressure at 20 °C: 8,300 hPa

- Density at 20 °C: 0.76 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not applicable.

- Solubility in / Miscibility with water: Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

- Dynamic: Not determined.
- Kinematic: Not determined.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 8)

| | |
|--------------------------------|--|
| · Solvent separation test: | Not applicable |
| · Solvent content: | |
| Organic solvents: | 86.4 % |
| Solids content: | 1.3 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

| | | |
|------------|----------|-----------------------|
| Dermal | LD50 | 89,268 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >112-115 mg/l (rat) |

67-64-1 acetone

| | | |
|------------|----------|--------------------------------|
| Oral | LD50 | 5,800 mg/kg (rat) (OECD 401) |
| | NOEL | 900 mg/kg (rat) |
| Dermal | LD50 | 15,688 mg/kg (rat) |
| | | >15,800 mg/kg (rht) |
| Inhalative | LC50/4 h | 76 mg/l (rat) |
| | NOAEL | 22,500 mg/m ³ (rat) |
| | LC50/48h | 8,450 mg/l (cru) |
| | | 2,262 mg/l (daphnia magna) |

115-10-6 dimethyl ether

| | | |
|------------|----------|---------------------------------|
| Inhalative | LC50/4h | 164,000 mg/m ³ (rat) |
| | LC50/4 h | 308 mg/l (rat) |
| | LC50/48h | >4,000 mg/l (daphnia magna) |

74-98-6 propane

| | | |
|------------|----------|----------------|
| Inhalative | LC50/4 h | >20 mg/l (rat) |
|------------|----------|----------------|

106-97-8 butane, pure

| | | |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 658 mg/l (rat) |
|------------|----------|----------------|

123-86-4 n-butyl acetate

| | | |
|------------|----------|-----------------------------------|
| Oral | LD50 | 10,800 mg/kg (rat) (OECD 423) |
| Dermal | LD50 | >17,600 mg/kg (rabbit) (OECD 402) |
| Inhalative | LC50/4 h | >21 mg/l (rat) (OECD 403) |

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 9)

| | | |
|---|-------------|----------------------------------|
| | LC50 | 390 mg/m ³ (rat) |
| | LC50/48h | 64 mg/l (Brachydanio rerio) |
| 75-28-5 isobutane | | |
| Inhalative | LC50/4 h | >50 mg/l (rat) |
| 7429-90-5 aluminium powder (stabilised) | | |
| Oral | LD50 | >2,000 mg/kg (rat) |
| Inhalative | LC50/4h | >888 mg/m ³ (rat) |
| | LC50/4 h | >5 mg/l (rat) |
| | NOAEC | 0.01 mg/l (rat) |
| reaction mass of ethylbenzole and xylene | | |
| Oral | LD50 | 3,523 mg/kg (rat) |
| | NOAEL-Werte | 250 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4h | 29,000 mg/m ³ (rat) |
| | LC50/4 h | 6.35-6.7 mg/l (rat) |
| 64-17-5 ethanol | | |
| Oral | LD50 | 10,470 mg/kg (rat) (OECD 401) |
| | NOAEL-Werte | >3,000 mg/kg (rat) (OECD 451) |
| Dermal | LD50 | >2,000 mg/kg (rabbit) (OECD 402) |
| Inhalative | LC50/4h | 20,000 mg/m ³ (rat) |
| | LC50/4 h | 120 mg/l (rat) (OECD 403) |
| | LC50/48h | 5,012 mg/l (ceriodaphnia Dubai) |
| | | 12,340 mg/l (daphnia magna) |
| | | 8,150 mg/l (Leuciscus idus) |

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

- Aquatic toxicity:

67-64-1 acetone

| | |
|----------|--|
| EC50/96h | 7,200 mg/l (green alge) |
| | 8,300 mg/l (piscis) |
| | 8,300 mg/l (lepomis macrochirus) |
| | 7,500 mg/l (selenastrum capricornutum) |
| EC50 | 1,700 mg/l (bacteria) |
| LC50 | 6,368 mg/l (piscis) |
| EC5/16h | 1,700 mg/l (pseudomonas putida) |

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 10)

| | |
|-----------|---|
| EC5/72h | 28 mg/l (Entosiphon sulcatum) |
| EC5/8d | 530 mg/l (Microcystis aeruginosa) |
| IC5/8d | 7,500 mg/l (Scenedesmus quadricauda) |
| EC50/48h | 3,400 mg/l (green alge) |
| | 8,800 mg/l (daphnia magna) |
| NOEC | 1,700 mg/kg (pseudomonas putida) |
| | 4,740 mg/kg (selenastrum capricornutum) |
| NOELR/28d | 2,212 mg/l (daphnia magna) |
| EC50/48h | 12,600 mg/l (Danio rerio.) |
| | 8,800 mg/l (daphnia magna) |
| LC50/96h | 8,300 mg/l (Iem) |
| | 8,300 mg/l (Iepomis macrochirus) |
| | 7,500 mg/l (Leuciscus idus) |
| | 5,540 mg/l (Oncorhynchus mykiss) |
| | 8,120 mg/l (Pimephales promelas) |

115-10-6 dimethyl ether

| | |
|----------|--|
| EC50/96h | 154.9 mg/l (green alge) |
| | >4,000 mg/l (poecilia reticulata) |
| | 154.917 mg/l (Pseudokirchneriella subcapitata) |
| EC50/48h | >4,000 mg/l (daphnia magna) |
| LC50/96h | >4,000 mg/l (poecilia reticulata) |

123-86-4 n-butyl acetate

| | |
|----------|--|
| EC50/24h | 72.8 mg/l (daphnia magna) (DIN 38412) |
| EC50/96h | 320 mg/l (green alge) |
| LC50/24h | 205 mg/l (daphnia magna) |
| IC50/72h | 648 mg/l (Desmodesmus subspicatus) |
| EC10/18h | 959 mg/l (pseudomonas putida) |
| EC50/48h | 44 mg/l (daphnia magna) |
| EC50/16h | 959 mg/l (pseudomonas putida) |
| NOEC | 200 mg/kg (Desmodesmus subspicatus) |
| NOEC/21d | 23 mg/l (daphnia magna) |
| EC50/72h | 647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest) |
| | 674 mg/l (Scenedesmus subspicatus) |
| LC50/96h | 62 mg/l (Danio rerio.) |
| | 81 mg/l (piscis) |
| | 100 mg/l (Iepomis macrochirus) |
| | 62 mg/l (Leuciscus idus) (DIN 38412) |
| | 18 mg/l (pimephales promelas) (OECD 203) |

reaction mass of ethylbenzole and xylene

| | |
|-----------|--------------------------------------|
| LC50/24h | 1 mg/l (daphnia magna) |
| EC50/48h | 3.2-9.5 mg/l (daphnia magna) |
| NOEC | 16 mg/l (BES) |
| | 1.3 mg/l (Oncorhynchus mykiss) |
| NOELR/72h | 0.44 mg/l (green alge) |
| NOELR/28d | 16 mg/l (bacteria) |
| EC50/72h | 2.2 mg/l (selenastrum capricornutum) |

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 11)

| | |
|------------------------|---|
| LC50/96h | 2.6 mg/l (Oncorhynchus mykiss) 8.9-16.4 mg/l (pimephales promelas) |
| 64-17-5 ethanol | |
| LC50/24h | 11,200 mg/l (Salmo gairdneri) |
| EC50/48h | 9,268-14,221 mg/l (daphnia magna) 12,900 mg/l (Selenastrum capricornutum) (OECD 201) |
| EC0 | 6,500 mg/l (pseudomonas putida) 5,000 mg/l (scenedesmus quadricauda) |
| EC10 | 11.5 mg/l (CHV) |
| EC50/72h | 275 mg/l (CHV) (OECD 201) |
| LC50/96h | 13,000 mg/l (Oncorhynchus mykiss) (OECD 203) 15,300 mg/l (pimephales promelas) |

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Other adverse effects**

No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

| | |
|-----------|---|
| 08 00 00 | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS |
| 08 01 00 | wastes from MFSU and removal of paint and varnish |
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |
| 15 00 00 | WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED |
| 15 01 00 | packaging (including separately collected municipal packaging waste) |
| 15 01 04 | metallic packaging |
| 15 00 00 | WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED |
| 15 01 00 | packaging (including separately collected municipal packaging waste) |
| 15 01 11* | metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers |

· **Uncleaned packaging:**

· **Recommendation:**

Non contaminated packagings may be recycled.
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· **Recommended cleansing agents:**

Alcohol

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

acetone

(Contd. of page 12)

SECTION 14: Transport information· **14.1 UN-Number**

· ADR, IMDG, IATA

UN1950

· **14.2 UN proper shipping name**

· ADR

1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· ADR



· Class

2.5F Gases.

· Label

2.1

· IMDG, IATA



· Class

2.1

· Label

2.1

· **14.4 Packing group**

· ADR, IMDG, IATA

Void

· **14.5 Environmental hazards:**

· Marine pollutant:

No

· **14.6 Special precautions for user**

· Hazard identification number (Kemler code):

Warning: Gases.

· EMS Number:

-

· Stowage Code

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1

litre: Category A. For AEROSOLS with a capacity above 1

litre: Category B. For WASTE AEROSOLS: Category C,

Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from" class 1

except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

(Contd. on page 14)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 13)

| | |
|-----------------------------------|--|
| · <u>Excepted quantities (EQ)</u> | Code: E0 Not permitted as Excepted Quantity |
| · <u>Transport category</u> | 2 |
| · <u>Tunnel restriction code</u> | D |
| · <u>IMDG</u> | 1L |
| · <u>Limited quantities (LQ)</u> | Code: E0 Not permitted as Excepted Quantity |
| · <u>Excepted quantities (EQ)</u> | |
| · <u>UN "Model Regulation":</u> | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- National regulations:
- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- VOC EU 702.5 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H220 Extremely flammable gas.
H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H261 In contact with water releases flammable gases.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2021

Version number 10

Revision: 22.01.2021

Trade name: Wheel Rim Silver

(Contd. of page 14)

· Recommended restriction of use· Department issuing SDS:· Contact:· Abbreviations and acronyms:

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.
refer to Technical Data Sheet (TDS)

Laboratory

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Water-react. 3: Substances and mixtures which in contact with water emit flammable gases – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 1: Acute toxicity – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

REACH directive 1907/2006/EC

· Sources· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC