

Technical Data Sheet

Page 1 of 2

Properties:	AKEMI® Thinner/Cleaner P is a product based on low boiling carboxylic acid esters. The product is characterized by the following qualities: - very high coverage if used as a thinner - very high cleaning and degreasing effect - very short evaporation time - evaporates without residue - free of reclaims - free of methanol, chlorinated hydrocarbons and paraffinic components
Application Area:	AKEMI® Thinner/Cleaner P is used to dilute AKEMI® Polyester Spray Filler (max. addition 5%). Furthermore, due to its composition the product is best suited to remove fresh sealants, 1-component paints, residues of impregnations as well as grease, oil, wax etc. It can also be used as a degreasing agent for stone surfaces, such as granite, limestone, ceramics etc. which have to be bonded afterwards.
Instructions for Use:	1. Use as a thinner for AKEMI® Polyester Spray Filler: a) Add maximum 5% of AKEMI® Thinner/Cleaner P. b) Stir the mixture homogenously, then pour into the spray gun and start working. 2. Use as a cleaner: a) Pour undiluted onto the surface and spread or apply with a cloth, a brush or a suitable pad. b) Let the product work for a short period of time and wipe off with a clean and lint-free cloth before the cleaner has evaporated.
Special Notes:	- For professional use only. - Use afin® Liquid Glove to protect your hands. - Not suitable for plastics and paints which are sensitive to solvents. Test the compatibility on an inconspicuous area before use. - Only use on cold surface. Warm surfaces extremely accelerate the evaporation of the solvent and thus reduce the cleaning effect. - For proper waste disposal the container must be completely emptied. - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
Technical Data:	Colour: colourless, clear Density: 0.9 g/cm³
Storage:	If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 36 months from production.
Health & Safety:	Read Safety Data Sheet before handling or using this product.

TDS 07.22

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 07.22