

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **AKEMIX 15**
- Article number: 30304
- UFI: 5QD0-20WT-N00K-R5QP

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Adhesives

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

- Flam. Liq. 2 H225 Highly flammable liquid and vapour.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word

Danger

Hazard-determining components of labelling:

butanone
Naphtha (petroleum), hydrotreated light acetone

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 1)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P261	Avoid breathing vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional information: Contains Rosin. May produce an allergic reaction.	

· Additional information:

· **2.3 Other hazards**

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Determination of endocrine-disrupting properties

78-93-3 butanone

List II

SECTION 3: Composition/information on ingredients· **3.2 Mixtures**

· Description: Mixture: consisting of the following components.

· Dangerous components:

CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-50%
CAS: 64742-49-0 EC number: 921-024-6 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35 01-2119475515-33	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	12.5-25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	12.5-25%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0 Reg.nr.: 01-2119474209-33-xxxx	n-hexane Flam. Liq. 2, H225 Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	<1%
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32-xxxx	Rosin Skin Sens. 1, H317	<1%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 2)

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Take affected persons out into the fresh air. Position and transport stably in side position.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately. Drink plenty of water and provide fresh air. Call for a doctor immediately. If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty
Headache
Dizziness
Dizziness
Gastric or intestinal disorders
Profuse sweating
Nausea
Danger of impaired breathing.

· Hazards**· 4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.
If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.

· 5.3 Advice for firefighters

- Protective equipment: Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases. Wear fully protective suit.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 3)

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat.

Prevent impact and friction.

Fumes can combine with air to form an explosive mixture.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in the original receptacle.

Prevent any seepage into the ground.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

· **Further information about storage conditions:**

Protect from frost.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· **Storage class:**

3

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 4)

· **7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection**· **8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:**78-93-3 butanone**

IOELV	Short-term value: 900 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm

67-64-1 acetone

IOELV	Long-term value: 1210 mg/m ³ , 500 ppm
-------	---

110-54-3 n-hexane

IOELV	Long-term value: 72 mg/m ³ , 20 ppm
-------	--

· DNELs**78-93-3 butanone**

Oral	DNEL (Langzeit-wiederholt)	31 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	1,161 mg/kg bw/day (ARB)
		412 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	600 mg/m ³ Air (ARB)
		106 mg/m ³ Air (BEV)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	DNEL (Langzeit-wiederholt)	699 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	773 mg/kg bw/day (ARB)
		699 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2,035 mg/m ³ Air (ARB)
		608 mg/m ³ Air (BEV)

67-64-1 acetone

Oral	DNEL (Langzeit-wiederholt)	62 mg/kg bw/day (BEV)	
Dermal	DNEL (Langzeit-wiederholt)	186 mg/kg bw/day (ARB)	
		62 mg/kg bw/day (BEV)	
Inhalative	DNEL (Kurzzeit-akut)	2,420 mg/m ³ Air (ARB)	
		DNEL (Langzeit-wiederholt)	1,210 mg/m ³ Air (ARB)
			200 mg/m ³ Air (BEV)

110-54-3 n-hexane

Dermal	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	5.3 mg/kg bw/day (BEV)
		75 mg/m ³ Air (ARB)

· PNECs**78-93-3 butanone**

PNEC (wässrig)	709 mg/l (KA)
	55.8 mg/l (MW)
	55.8 mg/l (SW)
	55.8 mg/l (WAS)
PNEC (fest)	22.5 mg/kg Trockengew (BO)
	284.7 mg/kg Trockengew (MWS)
	284.74 mg/kg Trockengew (SWS)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 5)

67-64-1 acetone

PNEC (wässrig)	100 mg/l (KA)
	1.06 mg/l (MW)
	10.6 mg/l (SW)
	21 mg/l (WAS)
PNEC (fest)	29.5 mg/kg Trockengew (BO)
	3.04 mg/kg Trockengew (MWS)
	30.4 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid close or long term contact with the skin.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter AX

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type.

The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

(Contd. on page 7)

EU

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 6)

- Material of gloves Butyl rubber, BR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Value for the permeation: Level \leq 2, 30 min
- For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
- As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
- Not suitable are gloves made of the following materials: Nitrile rubber, NBR
Neoprene gloves
Leather gloves
Strong material gloves
- Eye/face protection  Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- General Information
- Colour: Amber coloured
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 56 °C
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 0.6 Vol %
- Upper: 13 Vol %
- Flash point: -17 °C
- Ignition temperature: 465 °C
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity:
- Kinematic viscosity Not determined.
- Dynamic at 20 °C: 1,600 mPas
- Solubility
- water: Fully miscible.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 240 hPa
- Density and/or relative density
- Density at 20 °C: 0.83 g/cm³
- Relative density Not determined.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 7)

· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	75.9 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	
	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	
	Void
· Substances and mixtures, which emit flammable gases in contact with water	
	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications. No decomposition if used and stored according to specifications.
· 10.3 Possibility of hazardous reactions	Reacts with oxidising agents.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	Gaseous hydrocarbons, which can form explosive mixtures with air. Forms hydrochloric gas.

(Contd. on page 9)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 8)

SECTION 11: Toxicological information**· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**· Acute toxicity Based on available data, the classification criteria are not met.· LD/LC50 values relevant for classification:**78-93-3 butanone**

Oral	LD50	>2,193 mg/kg (rat) (OECD 423)
Dermal	LD50	>8,000 mg/kg (cuniculosus) >5,000 mg/kg (rbt) (OECD 402)
Inhalative	LC50/4 h	34 mg/l (rat)
	LC50/8h	23.5 mg/l (rat)
	LC50/48h	308 mg/l (daphnia magna)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	>2,920 mg/kg (rabbit)
Inhalative	LC50/4 h	>25 mg/l (rat)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
	NOEL	900 mg/kg (rat)
Dermal	LD50	15,688 mg/kg (rat) 7,426-15,800 mg/kg (rbt)
	NOAEL	22,500 mg/m ³ (rat)
Inhalative	LC50/4 h	76 mg/l (rat)
	LC50/48h	8,450 mg/l (cru) 2,262 mg/l (daphnia magna)

110-54-3 n-hexane

Oral	LD50	16,000 mg/kg (rat)
Dermal	LD50	3,350 mg/kg (rabbit)
Inhalative	LC50/4 h	169 mg/l (rat)
	LC50/1h	17.6 mg/l (rat)

- | | |
|--|---|
| · <u>Skin corrosion/irritation</u> | Causes skin irritation. |
| · <u>Serious eye damage/irritation</u> | Causes serious eye irritation. |
| · <u>Respiratory or skin sensitisation</u> | Based on available data, the classification criteria are not met. |
| · <u>Germ cell mutagenicity</u> | Based on available data, the classification criteria are not met. |
| · <u>Carcinogenicity</u> | Based on available data, the classification criteria are not met. |
| · <u>Reproductive toxicity</u> | Based on available data, the classification criteria are not met. |
| · <u>STOT-single exposure</u> | May cause drowsiness or dizziness. |
| · <u>STOT-repeated exposure</u> | Based on available data, the classification criteria are not met. |
| · <u>Aspiration hazard</u> | Based on available data, the classification criteria are not met. |

· 11.2 Information on other hazards· Endocrine disrupting properties

78-93-3 butanone

List II

(Contd. on page 10)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 9)

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****78-93-3 butanone**

EC5	1,150 mg/l (pseudomonas putida)
EC0	1,150 mg/l (pseudomonas putida) (DIN 38412)
IC5/7d	>4,300 mg/l (scenedesmus quadricauda)
EC50/48h	5,091 mg/l (daphnia magna) (OECD 202)
EC50/72h	1,972 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	3,220 mg/l (lem)
	2,993 mg/l (pimephales promelas) (OECD 203)

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50	1-10 mg/l (daphnia magna)
LC50	35-37 mg/l (piscis)
EC50/48h	3 mg/l (daphnia magna)
EL50/72h	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	>11.4 mg/l (Oncorhynchus mykiss)
NOELR/72h	3 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.17 mg/l (daphnia magna)

67-64-1 acetone

EC50/96h	7,200 mg/l (green alge)
	8,300 mg/l (piscis)
	8,300 mg/l (lepomis macrochirus)
	7,500 mg/l (selenastrum capricornutum)
EC50	1,700 mg/l (bacteria)
LC50	6,368 mg/l (piscis)
EC5/16h	1,700 mg/l (pseudomonas putida)
EC5/72h	28 mg/l (Entosiphon sulcatum)
EC5/8d	530 mg/l (Microcystis aeruginosa)
IC5/8d	7,500 mg/l (Scenedesmus quadricauda)
EC50/48h	3,400 mg/l (green alge)
	8,800 mg/l (daphnia magna)
NOEC	1,700 mg/kg (pseudomonas putida)
	4,740 mg/kg (selenastrum capricornutum)
NOELR/28d	2,212 mg/l (daphnia magna)
EC50/48h	12,600 mg/l (Danio rerio.)
	8,800 mg/l (daphnia magna)
LC50/96h	8,300 mg/l (lem)
	8,300 mg/l (lepomis macrochirus)
	7,500 mg/l (Leuciscus idus)
	5,540 mg/l (Oncorhynchus mykiss)
	8,120 mg/l (Pimephales promelas)

110-54-3 n-hexane

EL50/48h	21.85 mg/l (daphnia magna)
----------	----------------------------

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 10)

EL50/72h	9.285 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	12.51 mg/l (Oncorhynchus mykiss)
NOELR/21d	4.888 mg/l (daphnia magna)
NOELR/28d	2.8 mg/l (Oncorhynchus mykiss)
LC50/96h	2.5 mg/l (Pimephales promelas)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 11*	adhesive and sealant sludges containing organic solvents or other hazardous substances
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Solvent naphtha
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1133

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 11)

· 14.2 UN proper shipping name

· ADR 1133 ADHESIVES, special provision 640D
 · IMDG, IATA ADHESIVES

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.
 · Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
 · Label 3

· 14.4 Packing group

· ADR, IMDG, IATA II

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Warning: Flammable liquids.
 · Hazard identification number (Kemler code): 33
 · EMS Number: F-E, S-D
 · Stowage Category B

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)
 · Excepted quantities (EQ)

5L
 Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· Transport category 2
 · Tunnel restriction code D/E
 · Remarks: Packing group III, if content of packaging < 450 l, according 2.2.3.4 ADR

· IMDG

· Limited quantities (LQ)
 · Excepted quantities (EQ)

5L
 Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml
 Packing group III, if content of packaging < 30 l, according 2.3.2.3 IMDG

· Remarks:

· IATA

· Remarks: Packing group III, if content of packaging < 30l, according 3.3.3.1.1 IATA

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 12)

· UN "Model Regulation": UN 1133 ADHESIVES, 3, II

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone

3

67-64-1 acetone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone

3

67-64-1 acetone

3

· National regulations:· Information about limitation of use: Employment restrictions concerning juveniles must be observed.· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 629.6 g/l· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory

(Contd. on page 14)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022

Version number 12 (replaces version 11)

Revision: 19.12.2022

Trade name: AKEMIX 15

(Contd. of page 13)

<ul style="list-style-type: none"> · <u>Contact:</u> · <u>Date of previous version:</u> · <u>Version number of previous version:</u> · <u>Abbreviations and acronyms:</u> 	<p>Elke Hake Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de 09.12.2022</p> <p>11</p> <p>RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3</p>
---	---