

Tel. +49(0)911-642960 Fax. +49(0)911-644456

e-mail info@akemi.de

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Top Shield Black High-Performance Protection

· Article number: 12018

· UFI: M0UN-NM8V-E31S-G121

1.2 Relevant identified uses of the substance or mixture and

uses advised againstNo further relevant information available.

· Application of the substance / the

mixture Protective impregnation

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Lechstrasse 28 D 90451 Nürnberg

· Further information obtainable

from: Laboratory

1.4 Emergency telephone

number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008
 Flam. Liq. 3 H226 Flammable liquid and vapour.
 Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.

· <u>Storage:</u> Store in a well-ventilated place. Keep cool.

Store locked up.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 Hazard pictograms The product is classified and labelled according to the CLP regulation.







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of

<u>labelling:</u> 2,2,4,6,6-pentamethylheptan

Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

Hazard statements H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Page 2/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

(Contd. of page 1)
• Precautionary statements P101 If medical advice is needed, have product container or label at

hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P280 Wear eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/

doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

 $\begin{array}{ccc} \cdot & \underline{\mathsf{PBT:}} & & \mathsf{Not applicable.} \\ \cdot & \underline{\mathsf{vPvB:}} & & \mathsf{Not applicable.} \end{array}$

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture: consisting of the following components.

<u>Booonption.</u>	winkers. seriologing of the fellowing compensation.	
· Dangerous components:		
CAS: 13475-82-6 EINECS: 236-757-0 Reg.nr.: 01-2119490725-29	2,2,4,6,6-pentamethylheptan Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 EUH066	12.5-25%
EC number: 923-037-2 Reg.nr.: 01-2119471991-29-xxxx	Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	12.5-25%
CAS: 5593-70-4 EINECS: 227-006-8 Reg.nr.: 01-2119967423-33	tetra-n-butoxytitanium Flam. Liq. 3, H226 Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg.nr.: 01-2119433307-44	methanol Flam. Liq. 2, H225 Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: $C \ge 10\%$ STOT SE 2; H371: $3\% \le C < 10\%$	<1%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• <u>General information:</u> Take affected persons out into the fresh air.

Position and transport stably in side position.

After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



Page 3/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 2)

· After skin contact: If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a

doctor.

· After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and

delayed

Headache

Breathing difficulty Profuse sweating

Dizziness Dizziness Nausea

· Hazards Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special

treatment needed If s

If swallowed, gastric irrigation with added, activated carbon. If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• <u>6.4 Reference to other sections</u> See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Page 4/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Prevent any seepage into the ground.

Information about storage in one

common storage facility: Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions: Store receptacle in a well ventilated area.

Protect from frost.

· Storage class:

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
67-56-1 methanol		
IOELV	Long-term value: 260 mg/m³, 200 ppm Skin	
· <u>DNELs</u>		
5593-70-4 tetra-n-butoxytitanium		

Orai	DINEL (Langzeit-wiedernoit)	3.75 mg/kg bw/day (bev)
Dermal	DNEL (Langzeit-wiederholt)	37.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	127 mg/m³ Air (ARB)
		38 mg/m³ Air (BEV)

67-56-1 methanol

07 00 1 111	Cilianoi	, in an or			
Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)			
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)			
Dermal	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (ARB)			
		4 mg/kg bw/day (BEV)			
	DNEL (Langzeit-wiederholt)	20 mg/kg bw/day (ARB)			
		4 mg/kg bw/day (BEV)			
Inhalative	DNEL (Kurzzeit-akut)	130 mg/m³ Air (ARB)			
		26 mg/m³ Air (BEV)			
	DNEL (Langzeit-wiederholt)	130 mg/m³ Air (ARB)			
		26 mg/m³ Air (BEV)			

(Contd. on page 5)



Page 5/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Caustal as manua 1)

	(Contd. of page 4)			
· PNECs				
5593-70-4 tetra-	n-butoxytitanium			
PNEC (wässrig)	65 mg/l (KA)			
	0.008 mg/l (MW)			
	0.08 mg/l (SW)			
	2.25 mg/l (WAS)			
PNEC (fest)	0.017 mg/kg Trockengew (BO)			
	0.007 mg/kg Trockengew (MWS)			
	0.069 mg/kg Trockengew (SWS)			
67-56-1 methanol				
PNEC (wässrig)	100 mg/l (KA)			
	2.08 mg/l (MW)			
	20.8 mg/l (SW)			
	1,540 mg/l (WAS)			
PNEC (fest)	100 mg/kg Trockengew (BO)			
	7.7 mg/kg Trockengew (MWS)			
	77 mg/kg Trockengew (SWS)			
. Additional inform	votion: The lists valid during the making were used as basis			

Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic

Do not eat, drink, smoke or sniff while working. measures:

Apply solvent resistant skin cream before starting work.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

· Hand protection After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of

protective gloves:

STOKODERM (http://www.stoko.com)

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves: STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (http://www.stoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL

GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In

case of product dilution or in case of mixture with different substances or

(Contd. on page 6)



Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 5)

chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Fluorocarbon rubber (Viton) · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level < 6: 480 min

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are

suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890)

Butyl rubber, BR

· As protection from splashes gloves made of the following materials are

suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Chloroprene rubber, CR

Camapren (KCL, Art_No. 720, 722, 726)

Butoject (KCL, Art No. 897, 898) Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890) Butoject (KCL, Art No. 897, 898)

Butyl rubber, BR

· Not suitable are gloves made of

the following materials:

Natural rubber, NR Leather gloves

Strong material gloves

Goggles recommended during refilling · Eye/face protection

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: · Odour: Specific type · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range Undetermined. · Flammability Not applicable.

(Contd. on page 7)



Page 7/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 6)

•	Lower	and	upper	explosi	on limit
	-				

 · Lower:
 0.7 Vol %

 · Upper:
 10.4 Vol %

 · Flash point:
 42 °C

 · Ignition temperature:
 270 °C

Decomposition temperature:
 pH
 Not determined.
 Not determined.
 Not applicable

· Viscosity:

Kinematic viscosity
 Dynamic:
 Not determined.
 Not determined.

Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 10.7 hPa

Density and/or relative density

Density at 20 °C:
Relative density
Vapour density

0.87 g/cm³
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

· <u>Form:</u> Fluid

· Important information on protection of health and

environment, and on safety.

<u>Auto-ignition temperature:</u> Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Organic solvents: 50.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void
· Self-reactive substances and mixtures Void

Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

 \cdot Substances and mixtures, which emit flammable

gases in contact with water

Void

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

(Contd. on page 8)



Page 8/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 7)

SECTION 10: Stability and reactivity

· <u>10.1 Reactivity</u> No further relevant information available.

· 10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions

Reacts with strong oxidising agents.
Forms flammable gases/fumes.

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity
 Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
ATE (Acute Toxicity Estimates)			
Oral	LD50	22,447 mg/kg (rat)	
Dermal	LD50	67,340 mg/kg (rat)	
13475-82-6 2,2,4,6,6-pentamethylheptan			

		<u> </u>
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rat) (OECD 401) 2,200-2,500 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5 ppm (rat)
	LC50/48h	>3,193 mg/l (daphnia magna) (ISO 14559

Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5 mg/l (rat)
	LC50/48h	>1,000 mg/l (daphnia magna) (OECD 202)

5593-70-4 tetra-n-butoxytitanium

Oral	LD50	3,122 mg/kg (rat)
Dermal	LD50	5,300 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

67-56-1 methanol

Oral	LD50	100 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
		300 mg/kg (rat)
Inhalative	LC50/4 h	128.2 mg/l (rat)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

· <u>Serious eye damage/irritation</u> Causes serious eye irritation.

Respiratory or skin sensitisation
 Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

• STOT-single exposure Based on available data, the classification criteria are not met. • STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 8)

- · Aspiration hazard
- May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

12.1 TOXICITY			
	· Aquatic toxicity:		
	13475-82-6 2,2,4,6,6-pentamethylheptan		
		>1,000 mg/l (Pseudokirchneriella subcapitata)	
		>1,000 mg/l (daphnia magna)	
		1,000 mg/l (Pseudokirchneriella subcapitata) (OECD201)	
		0.02 mg/l (daphnia magna) (OECD 211)	
		0.267 mg/l (Oncorhynchus mykiss) ((Q)SAR)	
	EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)	
	LC50/96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)	
	Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics		
	EL0/48h	1,000 mg/l (daphnia magna)	
	EL0/72h	1,000 mg/l (Pseudokirchneriella subcapitata)	
	LL0/96h	1,000 mg/l (Oncorhynchus mykiss)	
	NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)	
	NOELR/21d	<1 mg/l (daphnia magna) (OECD 211)	
	NOELR/28d	0.192 mg/l (Oncorhynchus mykiss) ((Q)SAR)	
	EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)	
	LC50/96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)	
	5593-70-4 tetra-n-butoxytitanium		
	EC50/96h	225 mg/l (green alge)	
	EC50/48h	1,300 mg/l (daphnia magna)	
	NOEC/21d	4 mg/l (daphnia magna)	
	EC10	650 mg/l (bacteria)	
	LC50/96h	1,825 mg/l (piscis)	
67-56-1 me		nanol	
	EC50/96h	22,000 mg/l (Pseudokirchneriella subcapitata)	
	IC50	>1,000 mg/l (BES)	
	EC50/48h	>10,000 mg/l (daphnia magna)	
	LC50/96h	13,500-17,600 mg/l (lem)	
		19,500-20,700 mg/l (Oncorhynchus mykiss)	
		28,200 mg/l (pimephales promelas)	
_	· 12 2 Dorciet	ana and	

· 12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

(Contd. on page 10)



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 9)

· 12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

SECTION 14: Transport information

· <u>14.1 UN number or ID number</u> · <u>ADR, IMDG, IATA</u>	UN3295
· 14.2 UN proper shipping name · <u>ADR</u> · <u>IMDG, IATA</u>	3295 HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan) HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics, 2,2,4,6,6-pentamethylheptan)

· 14.3 Transport hazard class(es)

· ADR



 Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

14.4 Packing group

· ADR, IMDG, IATA Ш

· 14.5 Environmental hazards:

No · Marine pollutant:

· 14.6 Special precautions for user Warning: Flammable liquids.

30

· Hazard identification number (Kemler code): · EMS Number: F-E,S-D

(Contd. on page 11)



Page 11/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 10)

· <u>Stowage Category</u> A

· 14.7 Maritime transport in bulk according to IMO

<u>instruments</u> Not applicable.

· Transport/Additional information:

ADR

· Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· <u>Transport category</u> 3 · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) · Excepted quantities (EQ) 5L Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3295 HYDROCARBONS, LIQUID, N.O.S. (HYDROCARBONS, C10-C12, ISOALKANES, <2%)

AROMATICS, 2,2,4,6,6-PENTAMETHYLHEPTAN), 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation

(EC) No 1272/2008 GHS label elements

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.
Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the

application of lower-tier requirements

5,000 t

· Qualifying quantity (tonnes) for the

application of upper-tier

50.000 t

requirements REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3, 69

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 12)



AKEMI®

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.12.2022 Version number 3 (replaces version 2) Revision: 14.12.2022

Trade name: Top Shield Black High-Performance Protection

(Contd. of page 11)

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

 VOC EU 432.1 g/l

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Laboratory · Date of previous version: 14.12.2022

· Version number of previous

version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4