

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Lettering Primer Spray**

Article number: 11072

UFI: 6N84-505D-H00X-U2ST

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Priming

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
IF ON SKIN: Wash with plenty of water.
Storage: Store in a well-ventilated place. Keep cool.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store locked up.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word

Danger

Hazard-determining components of labelling:

acetone

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 1)

· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P260	Do not breathe spray.
	P280	Wear protective gloves / eye protection.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
· <u>Additional information:</u>	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
	EUH066	Repeated exposure may cause skin dryness or cracking. Contains 4-morpholinecarbaldehyde, maleic anhydride. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Buildup of explosive mixtures possible without sufficient ventilation.
· 2.3 Other hazards		
· Results of PBT and vPvB assessment		
· <u>PBT:</u>	Not applicable.	
· <u>vPvB:</u>	Not applicable.	

SECTION 3: Composition/information on ingredients**3.2 Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

67-64-1	acetone	25-50%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	
123-86-4	n-butyl acetate	<12.5%
	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	
74-98-6	propane	<12.5%
	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	
106-97-8	butane, pure	<10%
	Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	
75-28-5	isobutane	1-5%
	Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	

(Contd. on page 3)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 2)

9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	1-5%
	reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-5%
7779-90-0	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-5%
64-17-5	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319	1-5%
108-65-6	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	1-5%
13463-67-7	titanium dioxide Carc. 2, H351	1-5%
4394-85-8	4-morpholinecarbaldehyde Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty
Dizziness
Headache
Dizziness
Nausea
Danger of impaired breathing.

· Hazards

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:
Carbon monoxide (CO)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 3)

· **5.3 Advice for firefighters**

Formation of toxic gases is possible during heating or in case of fire.

· **Protective equipment:**

Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Mount respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
Mount respiratory protective device.
Ensure adequate ventilation
Keep away from ignition sources.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of the material collected according to regulations.
Ensure adequate ventilation.
Dispose contaminated material as waste according to item 13.
Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:**

VCI-Konzept für die Zusammenlagerung von Chemikalien beachten.
Store away from reducing agents.

· **Further information about storage conditions:**

Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

· **Storage class:**

2 B

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 4)

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetoneIOELV Long-term value: 1210 mg/m³, 500 ppm**123-86-4 n-butyl acetate**IOELV Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm**reaction mass of ethylbenzole and xylol**AGW Short-term value: 880 mg/m³, 200 ppm
Long-term value: 440 mg/m³, 100 ppm
H**108-65-6 2-methoxy-1-methylethyl acetate**IOELV Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin**· DNELs****67-64-1 acetone**

Oral	DNEL (Langzeit-wiederholt)	62 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	186 mg/kg bw/day (ARB) 62 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2,420 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	1,210 mg/m ³ Air (ARB) 200 mg/m ³ Air (BEV)

123-86-4 n-butyl acetate

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB) 6 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (ARB) 3.4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	600 mg/m ³ Air (ARB) 300 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	300 mg/m ³ Air (ARB) 102.34 mg/m ³ Air (BEV)

reaction mass of ethylbenzole and xylol

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	212 mg/kg bw/day (ARB) 108 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-442 mg/m ³ Air (ARB) 260 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	77 mg/m ³ Air (ARB) 14.8-65.3 mg/m ³ Air (BEV)

7779-90-0 trizinc bis(orthophosphate)

Oral	DNEL (Langzeit-wiederholt)	0.83 mg/kg bw/day (BEV)
------	----------------------------	-------------------------

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 5)

Dermal	DNEL (Langzeit-wiederholt)	83 mg/kg bw/day (ARB) 83 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	5 mg/m³ Air (ARB) 2.5 mg/m³ Air (BEV)

64-17-5 ethanol

Oral	DNEL (Langzeit-wiederholt)	87 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	950 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	343 mg/kg bw/day (ARB) 206 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,900 mg/m³ Air (ARB) 950 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	950 mg/m³ Air (ARB) 114 mg/m³ Air (BEV)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL (Langzeit-wiederholt)	1.67 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	153.5 mg/kg bw/day (ARB) 54.8 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	550 mg/m³ Air (ARB) 33 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	275 mg/m³ Air (ARB) 33 mg/m³ Air (BEV)

13463-67-7 titanium dioxide

Oral	DNEL (Langzeit-wiederholt)	700 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	10 mg/m³ Air (ARB)

· PNECs**67-64-1 acetone**

PNEC (wässrig)	100 mg/l (KA) 1.06 mg/l (MW) 10.6 mg/l (SW) 21 mg/l (WAS)
PNEC (fest)	29.5 mg/kg Trockengew (BO) 3.04 mg/kg Trockengew (MWS) 30.4 mg/kg Trockengew (SWS)

123-86-4 n-butyl acetate

PNEC (wässrig)	35.6 mg/l (KA) 0.018 mg/l (MW) 0.18 mg/l (SW) 0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO) 0.0981 mg/kg Trockengew (MWS) 0.981 mg/kg Trockengew (SWS)

reaction mass of ethylbenzole and xylol

PNEC (wässrig)	6.58 mg/l (KA) 0.327 mg/l (MW) 0.327 mg/l (SW)
PNEC (fest)	2.31 mg/kg Trockengew (BO)

(Contd. on page 7)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 6)

	12.46 mg/kg Trockengew (MWS) 12.46 mg/kg Trockengew (SWS)
64-17-5 ethanol	
PNEC (wässrig)	580 mg/l (KA) 0.79 mg/l (MW) 0.96 mg/l (SW) 2.75 mg/l (WAS)
PNEC (fest)	0.63 mg/kg Trockengew (BO) 0.72 mg/kg Trockengew (FUT) 2.9 mg/kg Trockengew (MWS) 3.6 mg/kg Trockengew (SWS)
108-65-6 2-methoxy-1-methylethyl acetate	
PNEC (wässrig)	100 mg/l (KA) 0.0635 mg/l (MW) 0.635 mg/l (SW) 6.35 mg/l (WAS)
PNEC (fest)	0.29 mg/kg Trockengew (BO) 0.329 mg/kg Trockengew (MWS) 3.29 mg/kg Trockengew (SWS)
13463-67-7 titanium dioxide	
PNEC (wässrig)	100 mg/l (KA) 1 mg/l (MW) 0.127 mg/l (SW)
PNEC (fest)	100 mg/kg Trockengew (BO) 100 mg/kg Trockengew (MWS) 1,000 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX

· Respiratory protection:

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 7)

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Butyl rubber, BR
Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level $\leq$ 1, 10 min

· As protection from splashes gloves made of the following materials are suitable:

Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)

· Not suitable are gloves made of the following materials:

Neoprene gloves
Nitrile rubber, NBR
Leather gloves
Strong material gloves

· Eye/face protection

Tightly sealed goggles

· Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties· **9.1 Information on basic physical and chemical properties**· General Information

· <u>Colour:</u>	According to product specification
· <u>Odour:</u>	Specific type
· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Boiling point or initial boiling point and boiling range</u>	Not applicable, as aerosol.
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	1.2 Vol %
· <u>Upper:</u>	13 Vol %
· <u>Flash point:</u>	Not applicable, as aerosol.
· <u>Ignition temperature:</u>	365 °C
· <u>pH</u>	Not determined.
	Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined.
	Not applicable

(Contd. on page 9)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 8)

· <u>Dynamic:</u>	Not determined. Not applicable
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Vapour pressure at 20 °C:</u>	8,300 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.84 g/cm ³

· 9.2 Other information

· <u>Appearance:</u>	
· <u>Form:</u>	Aerosol
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Auto-ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	In use, may form flammable/explosive vapour-air mixture.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	77.1 %
· <u>Solids content:</u>	14.5 %

· Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
	Void

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 9)

· Substances and mixtures, which emit flammable gases in contact with water

· Oxidising liquids Void

· Oxidising solids Void

· Organic peroxides Void

· Corrosive to metals Void

· Desensitised explosives Void

Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions**

No dangerous reactions known.

· **10.4 Conditions to avoid**

No further relevant information available.

· **10.5 Incompatible materials:**

No further relevant information available.

· **10.6 Hazardous decomposition products:**

No dangerous decomposition products known.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal	LD50	73,333 mg/kg
Inhalative	LC50/4 h	233-246 mg/l (rat)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
	NOEL	900 mg/kg (rat)
Dermal	LD50	15,688 mg/kg (rat)
		7,426-15,800 mg/kg (rbt)
Inhalative	LC50/4 h	76 mg/l (rat)
	NOAEL	22,500 mg/m ³ (rat)
	LC50/48h	8,450 mg/l (cru)
		2,262 mg/l (daphnia magna)

123-86-4 n-butyl acetate

Oral	LD50	10,800 mg/kg (rat) (OECD 423)
------	------	-------------------------------

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 10)

Dermal	LD50	>17,600 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)
	LC50	390 mg/m ³ (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)
74-98-6 propane		
Inhalative	LC50/4 h	>20 mg/l (rat)
106-97-8 butane, pure		
Inhalative	LC50/4 h	658 mg/l (rat)
75-28-5 isobutane		
Inhalative	LC50/4 h	>50 mg/l (rat)
reaction mass of ethylbenzole and xylene		
Oral	LD50	3,523 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m ³ (rat)
	LC50/4 h	6.35-6.7 mg/l (rat)
7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.7 mg/l (rat)
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat) (OECD 401)
	NOAEL-Werte	>3,000 mg/kg (rat) (OECD 451)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	20,000 mg/m ³ (rat)
	LC50/4 h	120 mg/l (rat) (OECD 403)
	LC50/48h	5,012 mg/l (ceriodaphnia Dubai)
		12,340 mg/l (daphnia magna)
		8,150 mg/l (Leuciscus idus)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	6,190 mg/kg (rat) (OECD 401)
	NOAEL-Werte	1,500 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
		>2,000 mg/kg (rat)
Inhalative	LC50/4h	>10,000 mg/m ³ (rat)
	LC50	>23.8 mg/l (rat)
	LC50/4 h	35.7 mg/l (rat)
	LC50/48h	100 mg/l (Desmodesmus subspicatus)
13463-67-7 titanium dioxide		
Oral	LD50	>5,010 mg/kg (rat)
	NOAEL	24,000 mg/kg (rat)
Dermal	LD50	>10,010 mg/kg (rht)
Inhalative	NOAEL	10 mg/m ³ (rat)
	LC50/48h	>100 mg/l (daphnia magna)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 11)

- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information· **12.1 Toxicity**

· Aquatic toxicity:

67-64-1 acetone

EC50/96h	7,200 mg/l (green alge)
	8,300 mg/l (piscis)
	8,300 mg/l (lepomis macrochirus)
	7,500 mg/l (senastrum capricornutum)
EC50	1,700 mg/l (bacteria)
LC50	6,368 mg/l (piscis)
EC5/16h	1,700 mg/l (pseudomonas putida)
EC5/72h	28 mg/l (Entosiphon sulcatum)
EC5/8d	530 mg/l (Microcystis aeruginosa)
IC5/8d	7,500 mg/l (Scenedesmus quadricauda)
EC50/48h	3,400 mg/l (green alge)
	8,800 mg/l (daphnia magna)
NOEC	1,700 mg/kg (pseudomonas putida)
	4,740 mg/kg (senastrum capricornutum)
NOELR/28d	2,212 mg/l (daphnia magna)
EC50/48h	12,600 mg/l (Danio rerio.)
	8,800 mg/l (daphnia magna)
LC50/96h	8,300 mg/l (lem)
	8,300 mg/l (lepomis macrochirus)
	7,500 mg/l (Leuciscus idus)
	5,540 mg/l (Oncorhynchus mykiss)
	8,120 mg/l (Pimephales promelas)

123-86-4 n-butyl acetate

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (green alge)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)
	674 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.)
	81 mg/l (piscis)

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 12)

	100 mg/l (Iepomis macrochirus) 62 mg/l (Leuciscus idus) (DIN 38412) 18 mg/l (pimephales promelas) (OECD 203)
reaction mass of ethylbenzole and xylene	
LC50/24h	1 mg/l (daphnia magna)
EC50/48h	3.2-9.5 mg/l (daphnia magna)
NOEC	16 mg/l (BES) 1.3 mg/l (Oncorhynchus mykiss)
NOELR/72h	0.44 mg/l (green alge)
NOELR/28d	16 mg/l (bacteria)
EC50/72h	2.2 mg/l (senastrum capricornutum)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss) 8.9-16.4 mg/l (pimephales promelas)
7779-90-0 trizinc bis(orthophosphate)	
EC50/48h	28.2 mg/l (daphnia magna)
ErC50/72h	<0.3 mg/l (Desmodesmus subspicatus)
EC50/48h	<1.7 mg/l (daphnia magna)
EC50/72h	0.28 mg/l (Senastrum capricornutum)
LC50/96h	<5.1 mg/l (Oncorhynchus mykiss)
64-17-5 ethanol	
LC50/24h	11,200 mg/l (Salmo gairdneri)
EC50/48h	9,268-14,221 mg/l (daphnia magna) 12,900 mg/l (Senastrum capricornutum) (OECD 201)
EC0	6,500 mg/l (pseudomonas putida) 5,000 mg/l (scenedesmus quadricauda)
EC10	11.5 mg/l (CHV)
EC50/72h	275 mg/l (CHV) (OECD 201)
LC50/96h	13,000 mg/l (Oncorhynchus mykiss) (OECD 203) 15,300 mg/l (pimephales promelas)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50	>100 mg/l (daphnia magna)
LC50	63.5 mg/l (Oryzias latipes)
EC50/48h	>500 mg/l (daphnia magna) (RL 67/548/EWG. Anhang V, C.2.)
ErC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC20/0.5h	>1,000 mg/l (BES) (OECD 209)
NOEC	47.5 mg/l (Oryzias latipes)
NOEC/21d	≥100 mg/l (daphnia magna)
EC10	>1,000 mg/l (BES)
LC50/96h	134 mg/l (Oncorhynchus mykiss) >1,000 mg/l (Oryzias latipes) 161 mg/l (Pimephales promelas)
13463-67-7 titanium dioxide	
EC50	>1,000 mg/l (bacteria)
EC50/48h	>100 mg/l (daphnia magna)
EC50/72h	16 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>100 mg/l (Oncorhynchus mykiss) >1,000 mg/l (pimephales promelas)

(Contd. on page 14)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 13)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 14)

· 14.3 Transport hazard class(es)**· ADR**

· Class
· Label

2 5F Gases.
2.1

· IMDG, IATA

· Class
· Label

2.1 Gases.
2.1

· 14.4 Packing group**· ADR, IMDG, IATA**

Void

· 14.5 Environmental hazards:**· Marine pollutant:**

No

· 14.6 Special precautions for user**· Hazard identification number (Kemler code):**

-

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of
living quarters.

· Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1
except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:**· ADR****· Limited quantities (LQ)**

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG**· Limited quantities (LQ)**

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

(Contd. on page 16)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray

(Contd. of page 15)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

3

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 701.4 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Laboratory
- Contact: Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Date of previous version: 17.03.2022
- Version number of previous version: 2

(Contd. on page 17)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: Lettering Primer Spray**· Abbreviations and acronyms:**

(Contd. of page 16)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 1: Flammable liquids – Category 1
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Sol. 1: Flammable solids – Category 1
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU