Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ZEPALCO (NL)
- · Article number: 10600001
- · **UFI**: 81XJ-DFGX-AK69-WK20
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC35 Washing and cleaning products (including solvent based products)
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- · Application of the substance / the mixture Cleaning material/ Detergent
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

ZEP ITALIA SRL

Piazzale Luigi Cadorna, 2

20123 Milano (MI) - Italy;

Via Nettunense Km. 25.000

04011 Aprilia (LT) - Italy

T: +39.06.926691

F: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

 $Fax:(NL) + 31\ 164\ 266\ 710\ (B) + 32\ 2\ 347\ 1395$

@: info@zepbenelux.com

Distributed in the UK by:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RD

United Kingdom

Tel: +44 (0)151 422 1000

Fax: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

· Further information obtainable from:

Customer Service

NL: Tel: +31 164 250 100 Fax: +31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· 1.4 Emergency telephone number:

NHS +44 0845 46 47 (England or Wales); +44 08454 24 24 24 (Scotland)

emergency number (europe): 112

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

 (Contd. on page 2)

– ÉU

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

Trade name: ZEPALCO (NL)

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5	ethanol	50-75%
EINECS: 200-578-6	Flam. Liq. 2, H225	
Index number: 603-002-00-5	Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43-xxxx	Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	
CAS: 67-63-0	propan-2-ol	2.5-5%
EINECS: 200-661-7	Flam. Liq. 2, H225	
Index number: 603-117-00-0	Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25-xxxx		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

EU

Version: 10 (replaces version 1) Printing date 09.11.2023 Revision: 09.11.2023

Trade name: ZEPALCO (NL)

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

No special precautions are necessary if used correctly.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Mechanical ventilation is not required for storage

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the

Oral	DNEL Long term-systemic	87 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	206 mg/kg human/day (consumer)
		343 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m.	3 114 mg/m3 (consumer)
		950 mg/m3 (worker)
	DNEL Long term local mg/m3	950 mg/m3 (consumer)
		1,900 mg/m3 (worker)
CAS: 67-6	3-0 propan-2-ol	
Oral	DNEL Long term-systemic	26 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	319 mg/kg human/day (consumer)
		888 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m.	3 89 mg/m3 (consumer)
		500 mg/m3 (worker)
PNECs		
CAS: 64-1	7-5 ethanol	
	shwater mg/L 0.96 m	g/L (-)

(Contd. on page 4)

Version: 10 (replaces version 1) Printing date 09.11.2023 Revision: 09.11.2023

Trade name: ZEPALCO (NL)

	(Contd. of page 3)
PNEC Freshwater sediment	3.6 mg/Kg (-)
PNEC Marine water sediment	2.9 mg/Kg (-)
PNEC Intermittent release	2.75 (-)
PNEC Soil	0.63 mg/Kg (-)
PNEC Sewage treatment Plant mg/L	580 mg/L (-)
CAS: 67-63-0 propan-2-ol	
PNEC Freshwater mg/L	140.9 mg/L
PNEC Marinewater mg/L	140.9 mg/L
PNEC Freshwater sediment	552 mg/Kg
PNEC Marine water sediment	552 mg/Kg
PNEC Intermittent release	140.9
PNEC Soil	28 mg/Kg

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Plastic gloves

- Not suitable are gloves made of the following materials: Strong material gloves
- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

· General Information

· Physical state Fluid · Colour: Colourless · Odour: Alcohol-like · Odour threshold: Not determined. · Melting point/freezing point: Undetermined. >103 °C Boiling point or initial boiling point and boiling range · Flammability Not applicable.

· Lower and upper explosion limit 3.5 Vol % · Lower: 15 Vol % · Upper: 19 °C · Flash point: 425 °C · Auto-ignition temperature: Decomposition temperature: Not determined. · pH at 20 °C 6(-/+0.5)

· Viscosity:

2.41 s (DIN 53211/4) Kinematic viscosity at 20 °C Not determined. Dynamic:

·Solubility

Fully miscible. · water: · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 59 hPa

(Contd. on page 5)

Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

Trade name: ZEPALCO (NL)

		(Contd. of page
Density and/or relative density		
Density at 20 °C:	$0.86 \text{ g/cm}^3 (+/-0.01)$	
Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of health and environment, and on safety.		
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard. Not determined	
Solvent content:	noi aeierminea.	
Organic solvents:	73.4 %	
Swiss VOC:	73.40 %	
Solids content:	0.0 %	
Change in condition	0.0 /0	
Evaporation rate	Not determined.	
Information with regard to physical hazard classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable gases	s in	
contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		· LD/LC50 values relevant for classification:	
CAS: 64-17-5 ethanol			
	LD50	7,060 mg/kg (Rat)	
Inhalative	LC50 / 4 h	20,000 mg/l (Rat)	
CAS: 67-63-0 propan-2-ol			
Oral .	LD50	>5,000 mg/kg (Rat) 13,900 mg/kg (rab)	
Dermal .	LD50	13,900 mg/kg (rab)	
Inhalative	LC50 / 4 h	46-73 mg/l (Rat) (Contd. on page 6	

(Contd. on page 6)

Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

Trade name: ZEPALCO (NL)

(Contd. of page 5)

12,000-19,000 mg/m3 (Rat) EC50/24 h > 1,000 mg/ltr (Daphnia magna (water flea))

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 64-17-5 ethanol

EC 50 / 48 h 10,800 mg/ltr (Daphnia magna (water flea))

CAS: 67-63-0 propan-2-ol

LC50 / 96 h 9,640 mg/ltr (fish)

>1,400 mg/ltr (Lepomus gobbosus (Zonnebaars))

6,550 mg/ltr (Pimephales promelas)

EC 50 / 48 h 2,285-13,299 mg/ltr (Daphnia magna (water flea))

- · 12.2 Persistence and degradability No further relevant information available.
- Other information: The product is biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

In accordance with the requirements of the RVO in the Act on Detergents and Cleansing Agents, tensides are biodegradable up

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations

_	· European waste catalogue	
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED	
15 01 00	packaging (including separately collected municipal packaging waste)	
15 01 02	plastic packaging	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	

(Contd. on page 7)

Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

Trade name: ZEPALCO (NL)

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation: Disposal in accordance with administrative provisions

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN1170
14.2 UN proper shipping name ADR IMDG IATA	1170 ETHANOL (ETHYL ALCOHOL) mixture, MOLTEN ETHANOL (ETHYL ALCOHOL) mixture, MOLTEN ETHANOL mixture
14.3 Transport hazard class(es) ADR, IMDG, IATA	
Class Label	3 Flammable liquids.
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D A
14.7 Maritime transport in bulk according to IM instruments	10 Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml
Transport category Tunnel restriction code	Maximum net quantity per outer packaging: 500 ml 2 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml

UN 1170 ETHANOL (ETHYL ALCOHOL) MIXTURE, 3, II, MOLTEN

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 2020/878 annex II of REACH;

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 12/18 (Seveso III);

· UN "Model Regulation":

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

 $National\ regulations$ - UK:

Regulation (EC) No 1272/2008 (CLP) amended by GB CLP (UK SI 2019/720 as amended). REACH Regulation (EC) No 1907/2006, amended by UK REACH (UK SI 2019/758 as amended).

(Contd. on page 8)

Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

Trade name: ZEPALCO (NL)

(Contd. of page 7)

Health and Safety at Work Act

The Control of Substances Hazardous to Health (COSHH) Regulations

UK Waste (Circular Economy) (Amendment) Regulations 2020

- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	73.4

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Classification according to Regulation (EC) No 1272/2008 Calculation method
- Department issuing SDS:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

Version: 10 (replaces version 1) Printing date 09.11.2023 Revision: 09.11.2023

Trade name: ZEPALCO (NL)

(Contd. of page 8)

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· Contact:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

- · Date of previous version: 02.12.2022
- · Version number of previous version: 1
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

WELL: The highest acceptable concentration

IOELV: Indicative occupational exposure limit values

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

(Contd. on page 10)

Printing date 09.11.2023 Version: 10 (replaces version 1) Revision: 09.11.2023

Trade name: ZEPALCO (NL)

(Contd. of page 9)

Annex: Exposure scenario

- · Short title of the exposure scenario ZEPALCO RTU
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

• Product category PC35 Washing and cleaning products (including solvent based products)

· Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

· Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity According to directions for use.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Indoor application.

Outdoor application.

Avoid contact with eyes.

- Other operational conditions affecting consumer exposure Keep out of the reach of children.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

· Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

- · Environmental protection measures
- · Water No special measures required.
- · Disposal measures

Disposal in accordance with administrative provisions

Ensure that waste is collected and contained.

- Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.